



PAINT, INTERIOR UNDERCOAT ENAMEL

MSDS Number

BHDGP

National Stock Number

8010-00-281-2809

Product Name

PAINT, INTERIOR UNDERCOAT ENAMEL

Manufacturer

GRAHAM PAINT AND VARNISH COMPANY INC

Product Identification

Product ID: PAINT, INTERIOR UNDERCOAT ENAMEL

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00-281-2809

MSDS Number: BHDGP

Responsible Party

GRAHAM PAINT & VARNISH COMPANY, INC.

4800 S. RICHMOND ST.

CHICAGO , IL 60632

US

Emergency Phone: 312-376-7676

Info Phone: 312-376-7676

Cage: E0554

Contractor

GRAHAM PAINT AND VARNISH CO INC

CHICAGO, IL 60632-2022

US

312-376-7676

Cage: 61945

Ingredients

MINERAL SPIRITS

CAS: 64742-88-7

Fraction By Weight: 27.8%

ACGIH TLV: 500 PPM

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Effects of Overexposure: EYE: SEVER IRRITATION, REDNESS, TEARING,
BLURRED VISION. SKIN: IRRITATION, DEFATTING,
AND DERMATITIS INHAL: CAUSE

NASAL AND RESPIRATORY IRRITATION: GASTROINTESTINAL IRRITATION
AND DIARRHEA

First Aid

First Aid: EYE: FLUSH WITH LARGE AMOUNTS OF WATER, GET MEDICAL ATTENTION
SKIN: WASH EXPOSED AREA WITH SOAP & WATER, USE
EMOLLIENT CREAM. INHALATION: REMOVE INDIVIDUALS TO
FRESH AIR: INGESTION: DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION



Fire Fighting

Flash Point Method:TCC
Flash Point:102F/38.89C
Lower Limits:6.0
Upper Limits:1.0
Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL
Fire Fighting Procedures:STRAIGHT WATER STREAMS WILL SPREAD OIL FIRES.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY MOVE ALONG GROUND AND BE IGNITED BY HEAT, PILOT LIGHTS, OR OTHER IGNITION SOURCES.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES, ABSORB ON INERT MATERIAL, DISPOSE OF IN A CLOSED CONTAINER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND OPEN FLAME

Exposure Controls

Respiratory Protection:AT CONCENTRATIONS EXCEEDING THE TLV, USE SELF CONTAINED BREATHING APPARATUS.
Ventilation:LOCAL EXHAUST PROVIDE SUFFICIENT VENTILATION
Protective Gloves:IMPERVIOUS MATERIAL
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:AS REQUIRED TO AVOID WETTING CLOTHES
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:315-380F
Vapor Pres:2MMHG @68F
Vapor Density:4.9
Spec Gravity:1.39-1.43
Evaporation Rate & Reference:70
Solubility in Water:INSOLUBLE
Appearance and Odor:WHITE OPAQUE LIQUID WITH SLIGHT ALIPHATIC ODOR
Percent Volatiles by Volume:**

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, & VARIOUS HYDROCARBONS

Disposal

Waste Disposal Methods:INCINERATION OR LAND FILL IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.