

TT-P-25E, WHITE 27875

MSDS Number

BHDGY

National Stock Number

8010-00-282-9414

Product Name

TT-P-25E, WHITE 27875

Manufacturer

TRIAD PAINT AND CHEMICAL CORP

Product Identification

Product ID:TT-P-25E, WHITE 27875

MSDS Date:01/01/1987

FSC:8010

NIIN:00-282-9414

MSDS Number: BHDGY

Responsible Party

TRIAD PAINT AND CHEMICAL CORP

810 EVERGREEN AVENUE

BROOKLYN , NY 11207

US

Emergency Phone: (718) 443-2778

Info Phone: (718) 443-2778

Cage: 33151

Contractor

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

201-437-6501

Cage: 33151

Ingredients

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 20.99%

ACGIH TLV: 100 PPM

AROMATIC 150

CAS: 64742-95-6

Fraction By Weight: 1.68%

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:INHALATION: CAUSE HEADACHE, DIZZINESS, AND

NAUSEA SKIN: CAN CAUSE DEFATTING
EYE: VAPORS MAY BE
IRRITATING TO EYES,NO SE, AND THROAT.

First Aid

First Aid:EYE: FLUSH WITH COOL RUNNING WATER FOR 15 MINUTES.
SKIN: WASH AFFECTED AREA WITH SOAP AND WATER.
INHALATION: PROVIDE FRESH AIR AND
TEST.I NGESTION: DO NOT INDUCE VOMITING. DRINK 1-2 GLASSES OF WATER
TO DILUTE. SEE A PHYSICIAN.

Fire Fighting

Flash Point Method:PMCC
Flash Point:105F/41C
Lower Limits:6.0
Upper Limits:1.0
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS. DO NOT
USE WATER!!
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,
SPARKS, AND OPEN FLAMES. VAPORS FORM EXPLOSIVE MIXTURE BETWEEN
UPPER & LOWER EXPLOSIVE UNITS.

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE ALL SOURCES OF
IGNITION. PICK UP SPILL IMMEDIATELY W/INERT ABSORBENT &
NON-SPARKING TOOLS. SAFELY DISPOSE OF SATURATED ABSORBENT(S) BY
IMMERSING IN WATER. WEAR PROTECTIVE CLOTHING DURING CLEAN UP.

Handling

Handling and Storage Precautions:AVOID OPEN FLAME, & SPARK
SOURCES.PROVIDE ADEQUATEVENTILATION. AVOID EXCESSIVE HEAT.
Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED
CONTACT WITH SKIN AND VAPORS

Exposure Controls

Respiratory Protection:ORGANIC CANNISTER MASK OR AIR PACK IF
VENTILATION IS INADEQUATE.
Ventilation:LOCAL EXHAUST IS RECOMMENDED
Protective Gloves:NEOPRENE RUBBER GLOVES
Eye Protection:CHEMICAL SAFETY GOGGLES
Supplemental Safety and Health
NK

Chemical Properties

HCC:F4
Vapor Pres:Vapor Density:4.8
Spec Gravity:1.43
Evaporation Rate & Reference:Solubility in Water:NEG.
Appearance and Odor:WHITE COLORED LIQUID. HYDROCARBON ODOR
Percent Volatiles by Volume:41.68

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, AND BASES
Stability Condition to Avoid:WARM STORAGE, IGNITION SOURCES.
Hazardous Decomposition Products:CO, CO2, SMOKE, TOXIC VAPORS, AND
FUMES

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.