PRIMER COAT, SYNTHETIC, RUST INHIB. LACQ RE

MSDS Number

BHDKD

National Stock Number

8010-00-292-1127

Product Name

PRIMER COAT, SYNTHETIC, RUST INHIB. LACQ RE

Manufacturer

CON LUX COATINGS INC

Product Identification

Product ID:PRIMER COAT, SYNTHETIC, RUST INHIB. LACQ RE
MSDS Date:10/25/1983
FSC:8010
NIIN:00-292-1127
MSDS Number: BHDKD

Responsible Party

CON-LUX COATINGS, INC.

226 TALMADGE ROAD

EDISON , NJ 08818-0847

US

Emergency Phone: 908-287-4000

Info Phone: 908-287-4000 / FAX 908-287-9288

Cage: 60189

Contractor

CON-LUX COATINGS INC

847

EDISON, NJ 08818-0847

US

732-287-4000

Cage: 60189

Ingredients

ZINC CHROMATE

CAS: 13530-65-9

RTECS: GB3290000

Fraction By Weight: 4.2%

OSHA PEL0.1 MG/M3 (CRO3)

ACGIH TLV: 0.01MG/M3(CR)A1;9192

VM&P NAPHTHA

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 28.1%

ACGIH TLV: 500 PPM

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 9.8%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:IRRITATIN OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS IN SOME INSTANCES, MAY IRRITATE RESPIRATORY TRACT & CAUSE HEADACHE OR DIZZINESS, WHICH IS NORMAL FOR SOLVENT B ASE PRODUCTS

First Aid

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WTR. IF INHALED, REMOVE TO FRESH AIR. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

Fire Fighting

Flash Point Method:TCC
Flash Point:50 F 10 C
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST
Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID PROLONGED BREATHING OF VAPORS. VENTILATE AREA. CLEAN UP WITHABSORBENT MATERIAL

Handling

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS
Other Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS

Exposure Controls

Respiratory Protection:OUTDOOR OR OPEN AREAS, USE NIOSH APPROVED FILTER RESPIRATOR TO REMOVE SOLID AIR-BORNE PARTICLES. IN RESTRICTED VENTILATION AREAS, USE NIOSH APPROVED CHEMICAL FILTERS TO REMOVE COMBINATION OF VAPORS
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN BELOW ACCEPTABLE LIMIT
Protective Gloves:REQUIRED FOR LG OR REPEATED EXPOSURE
Eye Protection:TO PROTECT AGAINST SPLASH OF LIQUIDS
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING
Supplemental Safety and Health
NK

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:243-245 F
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHR

Percent Volatiles by Volume:64.6

Stability

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE & FEDERALREGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.