

---

## **PRIMER COAT, SYNTHETIC, RUST INHIB. LACQ RE**

### **MSDS Number**

BHDKD

### **National Stock Number**

8010-00-292-1127

### **Product Name**

PRIMER COAT, SYNTHETIC, RUST INHIB. LACQ RE

### **Manufacturer**

CON LUX COATINGS INC

### **Product Identification**

Product ID:PRIMER COAT, SYNTHETIC, RUST INHIB. LACQ RE

MSDS Date:10/25/1983

FSC:8010

NIIN:00-292-1127

MSDS Number: BHDKD

### **Responsible Party**

CON-LUX COATINGS, INC.

226 TALMADGE ROAD

EDISON , NJ 08818-0847

US

Emergency Phone: 908-287-4000

Info Phone: 908-287-4000 / FAX 908-287-9288

Cage: 60189

### **Contractor**

CON-LUX COATINGS INC

847

EDISON, NJ 08818-0847

US

732-287-4000

Cage: 60189

### **Ingredients**

ZINC CHROMATE

CAS: 13530-65-9

RTECS: GB3290000

Fraction By Weight: 4.2%

OSHA PEL0.1 MG/M3 (CRO3)

ACGIH TLV: 0.01MG/M3(CR)A1;9192

VM&P NAPHTHA

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 28.1%

ACGIH TLV: 500 PPM

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 9.8%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Effects of Overexposure:IRRITATION OF EYES AND SKIN MAY OCCUR WITH  
OVEREXPOSURE. CONTINUED BREATHING OF VAPORS IN SOME INSTANCES, MAY  
IRRITATE RESPIRATORY TRACT & CAUSE HEADACHE OR DIZZINESS, WHICH  
IS NORMAL FOR SOLVENT BASE PRODUCTS

## First Aid

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. IF INHALED,  
REMOVE TO FRESH AIR. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

## Fire Fighting

Flash Point Method:TCC  
Flash Point:50 F 10 C  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST  
Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE  
EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED  
CONTAINERS IN VICINITY  
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN  
AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
PROLONGED BREATHING OF VAPORS. VENTILATE AREA. CLEAN UP  
WITH ABSORBENT MATERIAL

## Handling

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND  
PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS  
Other Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE  
OF NFPA CLASS II FLAMMABLE LIQUIDS

## Exposure Controls

Respiratory Protection:OUTDOOR OR OPEN AREAS, USE NIOSH APPROVED FILTER  
RESPIRATOR TO REMOVE SOLID AIR-BORNE PARTICLES. IN RESTRICTED  
VENTILATION AREAS, USE NIOSH APPROVED CHEMICAL FILTERS TO REMOVE  
COMBINATION OF VAPORS  
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN  
VOLUME AND PATTERN BELOW ACCEPTABLE LIMIT  
Protective Gloves:REQUIRED FOR LG OR REPEATED EXPOSURE  
Eye Protection:TO PROTECT AGAINST SPLASH OF LIQUIDS  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH  
CONTAMINATED CLOTHING  
Supplemental Safety and Health  
NK

## Chemical Properties

HCC:F3  
Boiling Pt:B.P. Text:243-245 F  
Vapor Density:> AIR  
Evaporation Rate & Reference:SLOWER THAN ETHR

Percent Volatiles by Volume:64.6

## Stability

Stability Indicator/Materials to Avoid:YES

NK

Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE & FEDERALREGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.