



---

## **YELLOW SG ALKYD ENAMEL 23538**

### **MSDS Number**

BHDKJ

### **National Stock Number**

8010-00-297-0585

### **Product Name**

YELLOW SG ALKYD ENAMEL 23538

### **Manufacturer**

EVERSEAL MFG CO INC

### **Product Identification**

Product ID:YELLOW SG ALKYD ENAMEL 23538

MSDS Date:04/07/1988

FSC:8010

NIIN:00-297-0585

MSDS Number: BHDKJ

### **Responsible Party**

EVERSEAL MFG CO INC

475 BROAD AVE

RIDGEFIELD , NJ 07657-2329

US

Emergency Phone: 201-943-4986

Info Phone: 201-943-4986 / FAX 201-943-1123

Cage: 72988

### **Contractor**

EVERSEAL MFG CO INC

RIDGEFIELD, NJ 07657-2329

US

201-943-4986

Cage: 72988

### **Ingredients**

RESIN

Fraction By Weight: 23%

OSHA PELNA

ACGIH TLV: NA

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 1 - 3%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR



CAS: 7758-97-6  
RTECS: GB2975000  
Fraction By Weight: 19%  
OSHA PEL0.05 MG/M3 (PB)  
ACGIH TLV: 0.05MG/M3(CR)A2;8990

TALC (CONTAINING NO ASBESTOS)  
CAS: 14807-96-6  
RTECS: WW2710000  
Fraction By Weight: 19%  
OSHA PEL2 MG/M3 RDUST  
ACGIH TLV: 2 MG/M3 RDUST; 9192

MINERAL SPIRITS  
CAS: 64475-85-0  
RTECS: PY8240000  
Fraction By Weight: 34%

ADDITIVES  
Fraction By Weight: 4%  
OSHA PELNA  
ACGIH TLV: NA

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Explanation of Carcinogenicity:IS A SUSPECTED CARCINOGEN UNDER FREQUENT & PROLONGED EXPOSURE.  
Effects of Overexposure:INHALATION:DIZZINESS,NAUSEA,POSSIBLE UNCONSCIOUSNESS.IRRITATING TO SKIN & EYES. FREQUENT/PROLONGED EXPOSURE TO LEAD CHROMATE DUST CAN CAUSE LIVER &/OR KIDNEY DAMAGE.SANDING,BLASTING,GRINDING OR WELDING OPERATIONS SHOULD BE PERFORMED ONLY IF ADEQUATE PRECAUTIONS ARE TAKEN.

## First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR.APPLY RESPIRATION IF NEEDED.SKIN:WASH W SOAP/WTR.EYES: FLUSH W/WTR CONSULT PHYSICIAN.

## Fire Fighting

Flash Point:105F 40.56C  
Upper Limits:1.0  
Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL  
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING MEDIUM.FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

## Accidental Release

Spill Release Procedures:ENSURE ADEQUATE VENTILATION.REMOVE IGNITION SOURCES.ABSORB SMALL SPILLS ON DRY ABSORPTION MATEIAL. USE SPARK-PROOF SCOOP FOR LARGER SPILLS.

## Handling

Handling and Storage Precautions:AVOID EXCESSIVE HEAT OR IGNITION SOURCES.  
Other Precautions:NPCA/HMIS RATING 3,2,O,H



---

## Exposure Controls

Respiratory Protection:FUME & DUST MASK OR AIR-SUPPLIED HOOD.  
Ventilation:ADEQUATE TO ENSURE LEL NOT ACHIEVED.  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES  
Other Protective Equipment:PROTECT SKIN W/CLOTHING OR BARRIER CREAM.  
Supplemental Safety and Health  
NK

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:323 - 390F  
Vapor Density:>AIR  
Evaporation Rate & Reference:Percent Volatiles by Volume:58

## Stability

Stability Indicator/Materials to Avoid:YES  
AVOID STRONG OXIDIZING MATERIAL  
Stability Condition to Avoid:NA  
Hazardous Decomposition Products:CARBON MONOXIDE &/OR CARBON DIOXIDE ON  
COMBUSTION.

## Disposal

Waste Disposal Methods:DISPOSE OF AS PER LOCAL & FEDERAL REGULATIONS  
FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.