
HEAT RESISTING ENAMEL BLACK 17038

MSDS Number

BHDKP

National Stock Number

8010-00-297-2014

Product Name

HEAT RESISTING ENAMEL BLACK 17038

Manufacturer

EVERSEAL MANUFACTURING CO INC

Product Identification

Product ID:HEAT RESISTING ENAMEL BLACK 17038

MSDS Date:05/12/1987

FSC:8010

NIIN:00-297-2014

MSDS Number: BHDKP

Responsible Party

EVERSEAL MANUFACTURING CO., INC.

475 BROAD AVENUE

RIDGEFIELD , NJ 07657

US

Emergency Phone: 201-943-4986

Cage: EO432

Contractor

EVERSEAL MFG CO INC

RIDGEFIELD, NJ 07657-2329

US

201-943-4986

Cage: 72988

Ingredients

RESIN

Fraction By Weight: 49%

OSHA PELNA

ACGIH TLV: NA

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 2%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000
Fraction By Weight: 47%
OSHA PEL120 PPM

ADDITIVES
Fraction By Weight: 2%
OSHA PELNA
ACGIH TLV: NA

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Effects of Overexposure: INHALATION: DIZZINESS, NAUSEA, POSSIBLE
UNCONSCIOUSNESS. IRRITATION TO SKIN & EYES.

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION
IF NECESSARY. EYES: FLUSH W/WTR. SKIN: WASH W/SOAP & WTR. CONSULT
PHYSICIAN.

Fire Fighting

Flash Point: 105F 40.56C
Upper Limits: 1
Extinguishing Media: FOAM, CARBON DIOXIDE CO2, DRY CHEMICAL
Unusual Fire/Explosion Hazard: WATER NOT A SUITABLE EXTINGUISHING
MEDIUM. FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

Accidental Release

Spill Release Procedures: REMOVE IGNITION SOURCES. ENSURE ADEQUATE
VENTILATION. ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE
SPARK - PROOF SCOOP FOR LARGER SPILLS.

Handling

Handling and Storage Precautions: AVOID EXCESSIVE HEAT & OPEN IGNITION
SOURCES.
Other Precautions: NPCA/HMIS RATING 3,2,0,H

Exposure Controls

Respiratory Protection: IF TLV MAY BE EXCEEDED, USE CARTRIDGE FUME MASK.
Ventilation: SUFFICIENT TO ENSURE LEL NOT ACHIEVED.
Protective Gloves: IMPERVIOUS
Eye Protection: GOGGLES
Other Protective Equipment: PROTECT SKIN W/CLOTHING OR BARRIER CREAM.
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt: B.P. Text: 323 - 390F
Vapor Density: >AIR
Evaporation Rate & Reference: Percent Volatiles by Volume: 57

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid: NA
Hazardous Decomposition Products: CARBON MONOXIDE &/OR CARBON DIOXIDE ON
COMBUSTION

Disposal

Waste Disposal Methods: DISPOSE OF AS PER LOCAL & FEDERAL REGULATIONS
FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.