

## **ENAMEL ALKYD LUSTERLESS OLIVE DRAB 34088**

### **MSDS Number**

BHDKR

### **National Stock Number**

8010-00-297-2113

### **Product Name**

ENAMEL ALKYD LUSTERLESS OLIVE DRAB 34088

### **Manufacturer**

CHEMRAY COATINGS CORP

### **Product Identification**

Product ID:ENAMEL ALKYD LUSTERLESS OLIVE DRAB 34088

MSDS Date:01/01/1987

FSC:8010

NIIN:00-297-2113

MSDS Number: BHDKR

### **Responsible Party**

CHEMRAY COATINGS, CORP.

209 N. MICHIGAN AVE.

KENILWORTH , NJ 07033

US

Emergency Phone: 201-245-1111

Info Phone: 201-245-1111

Cage: OBRN9

### **Contractor**

CHEMRAY COATINGS CORP.

NA

KENILWORTH, NJ 07033

US

800-924-9300

Cage: OBRN9

### **Ingredients**

PIGMENTS

Fraction By Weight: 43%

VEHICLE

Fraction By Weight: 20%

SOLVENTS RULE 66 MINERAL SPIRITS

CAS: 64742-88-7

Fraction By Weight: 37%

ACGIH TLV: 200 PPM

LEAD DRIERS (36% PB)

Fraction By Weight: .4%

ACGIH TLV: .05 MG/M3

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:HIGH VAPOR CONCENTRATION(OVER 1000 PPM)ARE IRRITATING TO THE EYES & RESPIRATORY TRACT,MAY CAUSE HEADACHES & DIZZINESS-PROLONG SKIN CONTACT IRRITATES.

## First Aid

First Aid:EYE:FLUSH W/WTR 15 MINS,OR UNTIL IRRITATION SUBSIDES.IF IRRITATION PERSISTS,CALLA PHYSICIAN.SKIN:REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY W/SOAP & WTR. INHALATION:IF OVERCOME BY VAPORS,REMOVE TO FRESH AIR,CALL PHYSICIAN.INGESTION:DO NOT INDUCE VOMITING, CALL PHYSICIAN.

## Fire Fighting

Flash Point Method:SCC

Flash Point:103F 39.44C

Lower Limits:.9

Upper Limits:7

Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL

Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED CONTAINERS W/WATER SPRAY, AVOID BREATHING VAPOR OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

## Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.ADD ABSORBENT(SAND,EARTH,SAWDUST)TO SPILL.VENTILATE AREA(OPEN WINDOWS,DOORS).IF LARGE SPILL,KEEP PRODUCT FROM ENTERING SEWERS AND WATERCOURSES BY DIKING.ADVISE AUTHORITIES IF PRODUCT HAS ENTERED.

## Handling

Handling and Storage Precautions:PROPER SHIPPING NAME - PAINT

HAZARDOUS CLASSIFICATION -- COMBUSTIBLE LIQUID - ID NO

UN1263.

Other Precautions:NONE

## Exposure Controls

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREA.

Ventilation:LOCAL EXHAUST EXPLOSION PROOF EQUIPMENT

Protective Gloves:CHEM-RESISTANT GLOVES

Eye Protection:SPLASH GOGGLES/FACE SHIELD

Other Protective Equipment:USE CHEM-RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEATED SKIN CONTACT.

Supplemental Safety and Health

NK

## Chemical Properties

Boiling Pt:B.P. Text:308F

Vapor Pres:25C Vapor Density:4.8

Spec Gravity:1.25

Evaporation Rate & Reference:.09

Solubility in Water:NEG

Appearance and Odor:OLIVE DRAB COLOR W/KEROSENE ODOR

Percent Volatiles by Volume:60%

## Stability

Stability Indicator/Materials to Avoid:YES

CAN REACT W/OXIDIZING MATERIALS WHEN HEATED TO DECOMPOSITION

Stability Condition to Avoid:HIGH TEMPERATURES OR HEATING

Hazardous Decomposition Products:CARBON MONOXIDE

---

## Disposal

Waste Disposal Methods: ASSURE CONFORMITY W/APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.