

ENAMEL ALKYD GLOSS(FOR EXT&INT)GREEN 14062

MSDS Number

BHDKX

National Stock Number

8010-00-298-2296

Product Name

ENAMEL ALKYD GLOSS(FOR EXT&INT)GREEN 14062

Manufacturer

CHEMRAY COATING CORP

Product Identification

Product ID:ENAMEL ALKYD GLOSS(FOR EXT&INT)GREEN 14062

MSDS Date:10/28/1988

FSC:8010

NIIN:00-298-2296

MSDS Number: BHDKX

Responsible Party

CHEMRAY COATING CORP

209 N MICHIGAN AVE

KENILWORTH , NJ 07033

US

Emergency Phone: 201-245-1111

Info Phone: 201-245-1111

Cage: 33832

Contractor

CHEMRAY COATING CORP

KENILWORTH, NJ 07033

US

201-245-1111

Cage: 33832

Ingredients

MINERAL SPIRITS

Fraction By Weight: 48%

ACGIH TLV: 200 PPM

LEAD AS (PB), LEAD PRIMER

Fraction By Weight: .2%

ACGIH TLV: .05 MG/M3

CHROME YELLOW AS (PB CR04)

Fraction By Weight: 9.8%

ACGIH TLV: .05 MG/M3

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:HIGH VAPOR CONCENTRATIONS (OVER 1000 PPM) ARE IRRITATING TO THE EYE & RESPIRATORY TRACT.MAY CAUSE HEADACHES & DIZZINESS-PROLONG SKIN CONTACT IRRITATES.
Explanation of Carcinogenicity:NA
Effects of Overexposure:NA
Medical Cond Aggravated by Exposure:NA

First Aid

First Aid:EYE CONTACT FLUSH W/WTR FOR 15 MINS OR UNTIL IRRITATION SUBSIDES.IF IRRITATION PERSISTS CALL A PHYSICIAN.SKIN CONTACT REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY W/SOAP & WTR.INHALATION IF OVERCOME BY VAPORS,REMOVE TO FRESH AIR,CALLPHYSICIAN.INGESTION DO NOT INDUCE VOMITING, CALL PHYSICIAN.

Fire Fighting

Flash Point Method:SCC
Flash Point:103F 39.44C
Lower Limits:.9
Upper Limits:7
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIP FOR ENCLOSED CONTAINERS W/WTR SPRAY, AVOID BREATHING OR FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED,USE WTR SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.KEEP FROM HEAT,SPARKS & OPEN FLAME.ASS ABSORBENT (SAND,EARTH,SAWDUCT)TO SPIL. VENTILATE AREA.IF LARGE SPILL KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSES BY DIKING.ADVISE AUTHORITIES IF PRODUCT HAS ENTERED.

Handling

Handling and Storage Precautions:PROPER SHIPPING NAME PAINT
HAZARDOUS CLASSIFICATION COMBUSTIBLE LIQUID ID NO UN1263
Other Precautions:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATION OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALAING THE CONTENTS MAY BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY IN CONFINED AREA.
Ventilation:LOCAL EXHAUST EXPLOSION PROOF EQUIPMENT.
Protective Gloves:CHEM-RESISTANT GLOVES
Eye Protection:SPLASH GOGGLES OR FACE SHIELD
Other Protective Equipment:USE CHEM RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEATED SKIN CONTACT.
Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER-USE & KEEP CONTAINER CLOSED WHENNOT IN USE.
Supplemental Safety and Health
NK

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:308F
Melt/Freeze Pt:M.P/F.P Text:Vapor Pres:25C
Vapor Density:4.8
Spec Gravity:1.02
Evaporation Rate & Reference:.09
Solubility in Water:INSOLUBLE
Appearance and Odor:DARK FOREST GREEN LIQUID W/KEROSENE ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
CAN REACT W/OXIDIZING MATERIALS WHEN HEATED TO DECOMPOSITION

Stability Condition to Avoid:HIGH TEMPERATURE

Hazardous Decomposition Products:CARBON MONOXIDE

Disposal

Waste Disposal Methods:ASSURE CONFORMITY W/APPLICABLE DISPOSAL REGULATIONS.DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.