

ENAMEL ALKYD GLOSS 16376 LIGHT GRAY

MSDS Number

BHDKY

National Stock Number

8010-00-298-2298

Product Name

ENAMEL ALKYD GLOSS 16376 LIGHT GRAY

Manufacturer

CON LUX COATINGS INC

Product Identification

Product ID:ENAMEL ALKYD GLOSS 16376 LIGHT GRAY

MSDS Date:06/21/1985

FSC:8010

NIIN:00-298-2298

MSDS Number: BHDKY

Responsible Party

CON-LUX COATINGS INC

226 TALMADGE RD

EDISON , NJ 08818-0847

US

Emergency Phone: 908-287-4000

Info Phone: 908-287-4000 / FAX 908-287-9288

Cage: 60189

Contractor

CON-LUX COATINGS INC

847

EDISON, NJ 08818-0847

US

732-287-4000

Cage: 60189

Ingredients

MINERAL SPIRITS

CAS: 64742-47-8

Fraction By Weight: 42.3%

ACGIH TLV: 500 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:IRRITATION OF EYES & SKIN MAY OCCUR

W/OVEREXPOSURE.CONTINUED BREATHING OF VAPORSIN SOME INSTANCES,MAY IRRITATE RESPIRATORY TRACT & CAUSE HEADACHE OR DIZZINESS, WHICH IS NORMAL FOR SOLVENT BASE PRODUCT S.

First Aid

First Aid:FLUSH SKIN & EYE CONTACT W/PLENTY OF WATER.IF INHALED,REMOVE TO FRESH AIR.IF IRRITATION PERSISTS,CONSULT A PHYSICIAN.

Fire Fighting

Flash Point Method:TCC
Flash Point:105F 40.56C
Lower Limits:1.0
Extinguishing Media:FOAM, CARBON DIOXIDE CO2, DRY CHEMICAL, WATER MIST
Fire Fighting Procedures:SMOTHER FLAMES W/ONE OF THE ABOVE
EXTINGUISHING MEDIA.WATER MAY BE USED TO COOL DOWN UNOPENED
CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT.DO NOT USE IN
AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID PROLONGED
BREATHING OF VAPORS.VENTILATE AREA.CLEAN UP W/ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED &
PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS.

Exposure Controls

Respiratory Protection:IN OUTDOOR OR OPEN AREAS,USE NIOSH APPROVED
FILTER RESPIRATOR TO REMOVE SOLID AIR-BORNE PARTICLES OF OVERSPRAY
DURING SPRAY APPLICATION.IN RESTRICTED VENT AREASUSE NIOSH APPROVED
CHEMICAL FILTERS DESI GNED TO REMOVE A COMBINATION OF PARTIC.
Ventilation:GENERAL DILUTION OR LOCAL EXHAUST
Protective Gloves:REQUIRED FOR LONG OR REPEATED EXPOSURE
Eye Protection:SAFETY EYEWEAR TO PROTECT AGAINST SPLASH
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT
W/CONTAMINATED CLOTHING.
Supplemental Safety and Health
NK

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:323F
Vapor Density:>AIR
Evaporation Rate & Reference:Percent Volatiles by Volume:59.7

Stability

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:CARBON MONOXIDE & CARBON DIOXIDE

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL,STATE & FEDERAL
REGULATIONS.DO NOT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.