



---

## **DOW CORNING (R) 90-006, 1/2 CATALYST**

### **MSDS Number**

BHDLN

### **National Stock Number**

8030-00-401-2662

### **Product Name**

DOW CORNING (R) 90-006, 1/2 CATALYST

### **Manufacturer**

DOW CORNING CORP

### **Product Identification**

Product ID:DOW CORNING (R) 90-006, 1/2 CATALYST

MSDS Date:10/15/1985

FSC:8030

NIIN:00-401-2662

Kit Part:Y

MSDS Number: BHDLN

### **Responsible Party**

DOW CORNING CORPORATION

SOUTH SAGINAW ROAD

MIDLAND , MI 48686

US

Emergency Phone: 517-496-5900

Info Phone: 517-496-5900

Preparer: JACK L. SHENEGER

Cage: 5D028

### **Contractor**

DOW CORNING CORP

AUBURN, MI 48611

US

517-496-4388

Cage: 71984

### **Ingredients**

DIBUTYLTIN DILAURATE

CAS: 77-58-7

RTECS: WH7000000

Fraction By Weight: 4%

OSHA PEL0.1 MG/M3

ACGIH TLV: 0.1 MG/M3

CHROMIUM TRIOXIDE

CAS: 1333-82-0

RTECS: GB6650000

Fraction By Weight: 5%



OSHA PEL0.1 MG/M3

ACGIH TLV: 0.1 MG/M3

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:SWALLOWING SUBSTANTIAL AMOUNTS MAY CAUSE SOME INJURY. THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. SKIN: LONG/REPEATED CONTACTS MAY CAUSE MODERATE IRRITATION & POSSIBLE MILD BURN.  
Effects of Overexposure:EYE: MAY IRRITATE SERIOUSLY W/MODERATE CORNEAL INJURY & CONSIDERABLE REDNESS LASTING A WEEK OR MORE.; SKIN: SGL EXPOSURE FOR SVL HRS MAY CAUSE SLIGHT REDDEN-ING.; INHAL: NO IRRITATION TO THROAT OR NOSE EXPECTED.; INGEST: AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS, DURING NORMAL OPERATIONS SHOULD NOT CAUSE INJURY.

## First Aid

First Aid:EYE: FLUSH WITH WATER FOR 15 MINUTES. OBTAIN IMMEDIATE MEDICAL ATTENTION. SKIN: WIPE OFF & FLUSH WITH WATER. OBTAIN MED. ATTN. IF IRRIT DEVELOPES/PRESIST.INHAL: NO PROBLEMINGST: NO PROBLEM

## Fire Fighting

Flash Point:>250F/121C  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:WATER, WATER FOG, CO2, DRY; CHEMICAL, FOAM, AND OTHER  
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS  
Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL

## Handling

Handling and Storage Precautions:STORE BELOW 90F/32C. USE REASONABLE CARE.

## Exposure Controls

Respiratory Protection:NONE REQUIRED  
Ventilation:MECHANICAL RECOMMENDED  
Protective Gloves:NONE  
Eye Protection:SAFETY GLASSES/CHEMICAL GOGGLES  
Other Protective Equipment:NONE  
Work Hygienic Practices:WASH BEFORE EATING, SMOKING, AND END OF SHIFT  
Supplemental Safety and Health  
TRACES OF FORMALDEHYDE & OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT TEMP. ABOVE 150C IN THE PRESENCE OF AIR. PROVIDE ADEQUATE VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES.

## Chemical Properties

Boiling Pt:B.P. Text:>300F/149C  
Melt/Freeze Pt:M.P/F.P Text:NA  
Vapor Pres:Vapor Density:NA  
Spec Gravity:1.05  
Evaporation Rate & Reference:Solubility in Water:Appearance and Odor:VERY LITTLE ODOR, PASTE LIKE, GREEN  
Percent Volatiles by Volume:

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZING MATERIAL CAN CAUSE A REACTION  
Stability Condition to Avoid:NA



Hazardous Decomposition Products: METAL OXIDES, SILICON DIOXIDE, CARBON DIOXIDE, & TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS

## **Disposal**

Waste Disposal Methods: FEDERAL, STATE, & LOCAL REGULATIONS CONCERNING HEALTH & POLLUTION BE REVIEWED TO DETERMINE APPROPRIATE DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.