

PIGMENTED EPOXY POLY,F151,GRAY KT,F9P1K

MSDS Number

BHDLQ

National Stock Number

8010-00-410-8460

Product Name

PIGMENTED EPOXY POLY,F151,GRAY KT,F9P1K

Manufacturer

SEAGRAVE COATINGS CORP OF VA SEAGUARD DIV

Product Identification

Product ID:PIGMENTED EPOXY POLY,F151,GRAY KT,F9P1K

MSDS Date:08/04/1988

FSC:8010

NIIN:00-410-8460

Kit Part:Y

MSDS Number: BHDLQ

Responsible Party

SEAGRAVE COATINGS CORP OF VA. SEAGUARD DIVISION

4030 SEAGUARD AVENUE

PORTSMOUTH , VA 23701

US

Emergency Phone: 1-800-424-9300

Info Phone: (804) 488-4411

Cage: 60163

Contractor

SHERWIN-WILLIAMS, SEAGUARD

PORTSMOUTH, VA 23704

US

757-397-2223

Cage: 60163

Ingredients

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 26.45%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

AROMATIC HYDROCARBON 100

CAS: 64742-95-6

Fraction By Weight: 17.51%

ACGIH TLV: 200 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:SKIN: IRRITATION, DERMATITIS, AND SEVERE BURNS
EYE: IRRITATE AND SEVERELY DAMAGE
BY SHORT CONTACT INHALATION: IRRITATE
TISSUE OF THE ENTIRE RESPIRATORY TRACT.

First Aid

First Aid:SKIN: FLUSH AREA THOROUGHLY W/WATER; REMOVE CONTAMINATED CLOTHING UNDER SAFETY SHOWER FOR GROSS CONTAMINATION. GET MEDICAL HELP IF LARGE SKIN AREA CONTACTED OR IRRITATION PERSISTS. INGESTION: GIVE DILUTED VINEGAR OR CITRUS JUICE TO DRINK. DO NOT INDUCE VOMITING FOLLOW WITH MILK OR OLIVE OIL, OR EGG WHITES AND WATER. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:SCC
Flash Point:115F/46.11C
Upper Limits:0.7
Extinguishing Media:CO2, WATER FOG, STEAM, FOAM, DRY CHEMICAL. COOL FIRE EXPOSE METAL CONTAINERS WITH A WATER SPRAY.
Fire Fighting Procedures:FIREFIGHTER MUST WEAR S.C.B.A. TO PROTECT AGAINST SOLVENT VAPORS AND NITROGEN CONTAINING DECOMPOSITION PRODUCTS.
Unusual Fire/Explosion Hazard:WHEN THIS MATERIAL IS INVOLVED IN A FIRE, TOXIC DEGRADATION PRODUCTS CAN BE PRODUCED INCLUDING CO2, CO, HCHO, AND SiO2.

Accidental Release

Spill Release Procedures:SCOOP OR SWEEP UP SOLID SPILLS FOR DISPOSAL OR RECOVERY. PICK UP LIQ SPILLS W/SAND OR ABSORBENT SOLID FOR LANDFILL DISPOSAL. FLUSH TRACES WITH WATER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF HEAT. PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE. PROPERLY VENT LIQUID STORAGE.
Other Precautions:STORE APPROVED LIQUID CONTAINERS IN A WELL VENTILATED LOW FIRE RISK AREA AWAY FROM COMBUSTIBLE AND CORROSIVE CHEMICALS. PREVENT SKIN CONTACT WITH PAINT.

Exposure Controls

Respiratory Protection:CHEMICAL CARTRIDGE RESPIRATOR OR AIR SUPPLIED OR SELF CONTAINED RESPIRATOR. A FULL FACE MASK IS NEEDED TO PREVENT EYE IRRITATION FROM VAPORS.
Ventilation:GENERAL/LOCAL EXHAUST TO KEEP WORK PLACE VAPORS AT A MINIMUM
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES/GOGGLES W/FACE SHIELD
Other Protective Equipment:LONG SLEEVE W/BUTTONED COLLAR; APRON; PROTECTIVE CREAM ON AREAS OF SKIN EXPOSED TO DUST.
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:244F
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NONE
Appearance and Odor:GRAY LIQUID, ALCOHOL AND NAPHTHA ODOR
Percent Volatiles by Volume:39

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.