

EA 956 PART B

MSDS Number

BHDLY

National Stock Number

8040-00-463-7042

Product Name

EA 956 PART B

Manufacturer

DIAL CORP THE

Product Identification

Product ID:EA 956 PART B

MSDS Date:01/10/1989

FSC:8040

NIIN:00-463-7042

Kit Part:Y

MSDS Number: BHDLY

Responsible Party

DIAL CORP THE

1865 DIAL TOWER

PHOENIX , AZ 85077-1865

US

Emergency Phone: 602-991-3000

Info Phone: 602-991-3000

Cage: 0EK45

Contractor

DIAL CORP THE

3223

PHOENIX, AZ 85077

US

602-991-3000

Cage: 0EK45

Ingredients

DIETHYLENE TRIAMINE

CAS: 111-40-0

RTECS: IE1225000

Fraction By Weight:

OSHA PEL1 PPM

ACGIH TLV: S, 1 PPM; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CORROSIVE TO SKIN AND EYES. CAN CAUSE
CHEMICAL BURNS TO SKIN AND SEVERE CHEMICALBURNS TO EYES. VAPORS
IRRITATING AND MAY CAUSE CHEST DISCOMFORT AND BRONCHITIS SYMPTOMS.
MODERATELY TOXIC BY INGESTION.

First Aid

First Aid:EYES: IRRI IMMED W/LARGE AMOUNTS OF WATER FOR A MIN OF 15 MINUTES. SEEK MED ATTNTN TO ASSESS NATURE/EXTENT OF INJURY. SKIN: WASH SKIN CONTACT IMMED W/COPIOUS AMTS SOAP/WATER. IF EXTENSIVE CONTACT USE EME RG SHOWER TO FLUSH W/LARGE AMTS RUNNINGWATER/SOAP FOR 15 MIN. REMOVE ALL CONTAM CLOTHING. INHALATION: REMOVE TO UNCON- TAM ATMOS/GET MED ATTN. INGESTION: IMMED DRINK LARGE AMTS WATER/MILK/MED ATTN.

Fire Fighting

Flash Point:>300F
Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASSES MAY BE LIBERATED.

Accidental Release

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. COVER WITH ABSORBENT MATERIAL, THEN SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UPREMAINING RESIDUE WITH SOLVENTS OBSERVING SOLVENT FLAMMABILITY CAUTIONS OR USE DETERGENT.

Handling

Handling and Storage Precautions:KEEP PRODUCT COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS.
Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

Exposure Controls

Respiratory Protection:NOT REQUIRED WITH GOOD INDUSTRIAL VENTILATION.
Ventilation:LOCAL EXHAUST RECOMMENDED. MECHANICAL RECOMMENDED.
Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER.
Eye Protection:SAFETY GLASSES OR GOGGLES.
Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.
Work Hygienic Practices:WASH WITH SOAP AND WATER.
Supplemental Safety and Health
KEY1:C2. KIT CONSISTS OF TWO PARTS. SEE PNI C FOR OTHER PART.

Chemical Properties

HCC:B2
Boiling Pt:B.P. Text:405F
Vapor Pres:0.37MM HG
Vapor Density:3.48,AIR=1
Spec Gravity:0.951, H2O=1
Evaporation Rate & Reference:LOW
Solubility in Water:100%
Appearance and Odor:AMBER LIQUID WITH AMMONIACAL ODOR.
Percent Volatiles by Volume:LOW

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.
Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.
Conditions to Avoid Polymerization:AVOID MIXING RESIN/CURING AGENT IN BATCHES > 1 LB TOTAL. DO NOT HEAT MIXED ADHESIVE >75F UNLESS CURING SURFACES BONDED.

Disposal

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO D.O.T. HAZARD CLASS. IF NOT REGULATED BY D.O.T., DISPOSE OF AS ORM-E. DISPOSAL METHOD CAN BE LAND BURIAL ORCHEMICAL INCINERATION AS REGULATED BY ALL GOVERNMENTAL AGENCIES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.