

BLACK GLOSS ALKYD ENAMEL 17038

MSDS Number

BHDMP

National Stock Number

8010-00-527-2050

Product Name

BLACK GLOSS ALKYD ENAMEL 17038

Manufacturer

EVERSEAL MANUFACTURING CO INC

Product Identification

Product ID:BLACK GLOSS ALKYD ENAMEL 17038

MSDS Date:05/26/1987

FSC:8010

NIIN:00-527-2050

MSDS Number: BHDMP

Responsible Party

EVERSEAL MANUFACTURING CO., INC.

475 BROAD AVENUE

RIDGEFIELD , NJ 07657

US

Emergency Phone: 201-943-4986

Cage: EO432

Contractor

EVERSEAL MFG CO INC

RIDGEFIELD, NJ 07657-2329

US

201-943-4986

Cage: 72988

Ingredients

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 3 - 5%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 55%

ACGIH TLV: 120 PPM

RESIN

Fraction By Weight: 41%

OSHA PELNA

ACGIH TLV: NA

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Effects of Overexposure:INHALATION: DIZZINESS, NAUSEA, POSSIBLE
UNCONSCIOUSNESS SKIN/EYE: IRRITATION

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION
IF NECESSARY. EYE: FLUSH WITH WATER
SKIN: WASH WITH SOAP AND WATER.
CONSULT A PHYSICIAN.

Fire Fighting

Flash Point:105F/40.56C

Lower Limits:1

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING
MEDIUM. FIREFIGHTERS SHOULD WEAR A SELF CONT-AINED BREATHING
APPARATUS.

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES, ENSURE ADEQUATE
VENTILA- TION. ABSORB SMALL SPILLS ON DRY ABSORPTION MATL. USE
SPARK PROOF SCOOP FOR LARGER SPILLS.

Handling

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION
SOURCES.

Other Precautions:NPCA/HMIS RATING 3,2,0,H

Exposure Controls

Respiratory Protection:IF TLV MAY BE EXCEEDED. USE CARTRIDGE MASK

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM.

Supplemental Safety and Health

NK

Chemical Properties

Boiling Pt:B.P. Text:323-390F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:65

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NA

Hazardous Decomposition Products:CARBON MONOXIDE/DIOXIDE

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL AND LOCAL
REGULATIONS FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.