

12197 ORANGE ENAMEL TT-E-489

MSDS Number

BHDMT

National Stock Number

8010-00-527-3200

Product Name

12197 ORANGE ENAMEL TT-E-489

Manufacturer

EVERSEAL MFG CO INC

Product Identification

Product ID:12197 ORANGE ENAMEL TT-E-489

MSDS Date:01/21/1987

FSC:8010

NIIN:00-527-3200

MSDS Number: BHDMT

Responsible Party

EVERSEAL MFG CO INC

475 BROAD AVE

RIDGEFIELD , NJ 07657-2329

US

Emergency Phone: 201-943-4986

Info Phone: 201-943-4986 / FAX 201-943-1123

Cage: 72988

Contractor

EVERSEAL MFG CO INC

RIDGEFIELD, NJ 07657-2329

US

201-943-4986

Cage: 72988

Ingredients

DNA ORANGE

CAS: 3468-63-1

RTECS: QL3854000

Fraction By Weight: 10%

ACGIH TLV: NA

YELLOW IRON OXIDE

CAS: 1309-37-1

Fraction By Weight: 1.5%

OSHA PEL10 MG/M3 (FE)

ACGIH TLV: 5 MG/M3(FE),B2; 9293

TTR266 TYPE III ALKYD

Fraction By Weight: 36%

ACGIH TLV: NA

MINERAL SPIRITS RULE 66

CAS: 64742-88-7

Fraction By Weight: 50%

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHAL; HIGH VAPOR CONCENTRATION MAY HAVE RESULTS OF DIZZINESS, HEADACHES, UN- CONSCIOUSNESS. PROLONGED OR REPEATED LIQUID CONTACT, WILL DRY, DEFAT SKIN, LEAD TO IRRITATION AND DERMATITIS

Effects of Overexposure:DRY AND DEFAT SKIN, LEADING TO IRRITATION AND DERMATITIS

Medical Cond Aggravated by Exposure:TROUBLE BREATHING, BREATHING, SKIN AND EYES

First Aid

First Aid:OVERCOME BY VAPOR, REMOVE FROM EXPOSURE, SEEK A PHYSICIAN. IF BREATHING IS IRREGULAR OR STOPPED, START RESUSCITATION, ADMINISTER OXYGEN. INGESTED; DO NOT INDUCE VOMITING; CALL A PHYSICIAN. SKIN CONTA CT; REMOVE ANY CONTAMINATED CLOTHS ANDWASH SKIN W/SOAP & WTR 15 MIN. OR UNTIL IRRITATION SUBSIDES

Fire Fighting

Flash Point Method:TCC

Flash Point:105 F / 40.56

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE UNSUITABLE EXCEPT AS A COOLING AGENT

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP PEOPLE RECOVER FREE LIQUID. ADD ABSORBENT (SAND, EARTH, SAWDUST, ETC.) TO SPILL AREA. AVOID BREATHING. VENTILATE SPACES. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES

Handling

Other Precautions:AVOID BREATHING VAPORS, AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE

Exposure Controls

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OF SUPPLIED AIR RESPIRATORY PROTECTION IN CON- FINED OR ENCLOSED SPACES IF NEEDED

Ventilation:USE EXPLOSION PROOF EQUIPMENT

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SPLASH GOGGLES OR FACE SHEILD

Other Protective Equipment:CHEMICAL RESISTANT APRON OR OTHER CLOTHING IF NEEDED TO AVOID PROLONGED SKIN CONTACT

Supplemental Safety and Health

AVOID BREATHING VAPORS. PROLONGED REPEATED CONTACT WITH SKIN

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:326-387

Vapor Pres:5MM

Vapor Density:4.9

Spec Gravity:.95

Evaporation Rate & Reference:.1

Appearance and Odor:STANDARD PAINT ODOR
Percent Volatiles by Volume:25

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS; LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM OR
CALCIUM HYPOCHLORIDE
Hazardous Decomposition Products:FUMES, SMOKE & CARBON MONOXIDE, IN THE
CASE OF INCOMPLETE COMBUSTION

Disposal

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL
REGULATIONS. DISPOSE ABSORBED MATERIAL AT DISPOSAL SITE OR
FACILITY

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.