

VARNISH TT-V-85

MSDS Number

BHDPG

National Stock Number

8010-00-597-3636

Product Name

VARNISH TT-V-85

Manufacturer

TRIAD PAINT AND CHEMICAL CORP

Product Identification

Product ID: VARNISH TT-V-85

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00-597-3636

MSDS Number: BHDPG

Responsible Party

TRIAD PAINT AND CHEMICAL CORP

810 EVERGREEN AVENUE

BROOKLYN , NY 11207

US

Emergency Phone: (718) 443-2778

Info Phone: (718) 443-2778

Cage: 33151

Contractor

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

Cage: 33151

Ingredients

MINERAL SPIRITS

CAS: 64741-41-9

Fraction By Weight: 57.3%

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Effects of Overexposure: VAPORS MIGHT BE IRRITATING TO EYES, NOSE, AND THROAT. EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS, AND NAUSEA. DEFATTING TO SKIN.

First Aid

First Aid: INHALATION: PROVIDE FRESH AIR AND REST. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. DRINK ONE OR TWO GLASSES OF WATER TO DILUTE. SEE PHYSICIAN. EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES.

Fire Fighting

Flash Point:41C 108F
Lower Limits:6.0
Upper Limits:1.0
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:FIREFIGHTER SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS. DO NOT USE WATER.
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAMES. VAPORS FORM EXPLOSIVE MIXTURE BETWEEN UPPER AND LOWER EXPLOSIVE UNITS.

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PICK UP SPILL IMMEDIATELY WITH INERT ABSORBENT(S) AND NON-SPARKING TOOLS. SAFELY DISPOSE OF SATURATED ABSORBENT(S) BY IMMERSING IN WATER. WEAR PROTECTIVE CLOTHING DURING CLEAN UP.

Handling

Handling and Storage Precautions:AVOID OPEN FLAME AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT.
Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED/REPEATED CONTACT WITH SKIN. AVOID REPEATED/PROLONGED BREATHING OF VAPORS.

Exposure Controls

Respiratory Protection:ORGANIC CANNISTER MASK OR AIR PACK IF VENTILATION IS INADEQUATE.
Ventilation:LOCAL EXHAUST IS RECOMMENDED. MECHANICAL WITH APPROVED CLASSV EXPLOSION PROOF MOTOR AND SWITCHES
Protective Gloves:NEOPRENE RUBBER GLOVES
Eye Protection:CHEMICAL SAFETY GLASSES
Supplemental Safety and Health
NK

Chemical Properties

Vapor Pres:100F
Vapor Density:5.0
Spec Gravity:.92
Evaporation Rate & Reference:.13
Solubility in Water:NEGLIGIBLE
Appearance and Odor:HAZY COLORED LIQUID, HYDROCARBON ODOR
Percent Volatiles by Volume:66.5

Stability

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS, STRONG ACIDS, AND LASERS
Stability Condition to Avoid:WARM STORAGE AND IGNITION SOURCES
Hazardous Decomposition Products:CO, CO2, SMOKE, TOXIC VAPORS, FUMES

Disposal

Waste Disposal Methods:DISPOSAL METHODS MUST COMPLY WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.