

TT-P-91D, TY2, AMD 2

MSDS Number

BHDPK

National Stock Number

8010-00-597-8199

Product Name

TT-P-91D, TY2, AMD 2

Manufacturer

TRIAD PAINT AND CHEMICAL CORP

Product Identification

Product ID:TT-P-91D, TY2, AMD 2

MSDS Date:01/01/1987

FSC:8010

NIIN:00-597-8199

MSDS Number: BHDPK

Responsible Party

TRIAD PAINT AND CHEMICAL CORP

810 EVERGREEN AVENUE

BROOKLYN , NY 11207

US

Emergency Phone: (718) 443-2778

Info Phone: (718) 443-2778

Cage: 33151

Contractor

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

201-437-6501

Cage: 33151

Ingredients

MINERAL SPIRITS

CAS: 64741-41-9

ACGIH TLV: 100 PPM

CELLOSOLVE ACETATE

CAS: 111-15-9

RTECS: PJ4375000

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:VAPORS MIGHT BE IRRITATING TO EYES,
NOSE & THROAT. EXCESSIVE EXPOSURE MAY RESULTIN HEADACHE,
DIZZINGESS, & NAUSEA. DEFATTING TO SKIN.

Effects of Overexposure:VAPORS MIGHT BE IRRITATING TO EYES, NOSE &

THROAT. EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS, & NAUSEA. DEFATTING TO SKIN

First Aid

First Aid: INHALATION: PROVIDE FRESH AIR, AND REST. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. SEE A PHYSICIAN. AND EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES.

Fire Fighting

Flash Point: 105 F 41 C
Lower Limits: 1.0
Upper Limits: 7.0
Extinguishing Media: CO₂, DRY CHEMICAL, AND FOAM
Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS. DO NOT USE WATER.
Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAMES. VAPORS FORM EXPLOSIVE MIXTURE BETWEEN UPPER AND LOWER EXPLOSIVE UNITS

Accidental Release

Spill Release Procedures: VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PICK UP SPILL IMMEDIATELY WITH INERT ABSORBENT(S) & NON-SPARKING TOOL. SAFELY DISPOSE OF SATURATED ABSORBENTS BY IMMERSING IN WATER. WEAR PROTECTIVE CLOTHING DURING CLEAN-UP

Handling

Handling and Storage Precautions: AVOID OPEN FLAME AND SPARKS SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT
Other Precautions: DO NOT TAKE INTERNALLY. AVOID PROLONGED/REPEATED CONTACT WITH SKIN. AND AVOID PROLONGED/REPEATED BREATHING OF VAPORS

Exposure Controls

Respiratory Protection: ORGANIC CARTRIDGE MASK OR AIR PACK IF VENTILATION IS INADEQUATE
Ventilation: LOCAL IS RECOMMENDED AND MECHANICAL WITH APPROVED EXPLOSION PROOF MOTOR AND SWITCHES
Protective Gloves: NEOPRENE RUBBER GLOVES
Eye Protection: CHEMICAL SAFETY GOGGLES
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt: B.P. Text: 313-382 F
Spec Gravity: 1.12
Evaporation Rate & Reference: .2
Solubility in Water: NEGLIGIBLE
Appearance and Odor: GRAY COLORED LIQUID. SWEET ODOR
Percent Volatiles by Volume: 68.7

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES
Stability Condition to Avoid: WARM STORAGE AND IGNITION SOURCES
Hazardous Decomposition Products: CO, CO₂, SMOKE, TOXIC VAPORS, FUMES AND CARBON TETRACHLORIDE

Disposal

Waste Disposal Methods: DISPOSAL METHOD MUST COMPLY WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.