

## **PAINT, OIL, CONCRETE & MASONRY (ALL COLORS)**

### **MSDS Number**

BHDPS

### **National Stock Number**

8010-00-598-5154

### **Product Name**

PAINT, OIL, CONCRETE & MASONRY (ALL COLORS)

### **Manufacturer**

S L GILLMAN PAINT COMPANY

### **Product Identification**

Product ID:PAINT, OIL, CONCRETE & MASONRY (ALL COLORS)

MSDS Date:07/14/1988

FSC:8010

NIIN:00-598-5154

MSDS Number: BHDPS

### **Responsible Party**

S.L. GILLMAN PAINT COMPANY

2250 MORELAND AVE. SE.

ATLANTA , GA 30315

US

Emergency Phone: 404-509-4400

Info Phone: 404-622-1326

Cage: OO269

### **Contractor**

S.L. GILLMAN PAINT COMPANY

ATLANTA

404 622 1326

Cage: OO269

### **Ingredients**

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 35-40%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ASPIRATION OF MATERIAL INTO THE LUNGS  
CAN CAUSE CHEMICAL PNEUMONHITIES WHICH CANBE FATAL.

PROLONGED/REPEATED CONTACT CAN CAUSE MODERATE IRRITATION,  
DEFATTING, DERMATITIS. BREATHING CAN CAUSE ASPHYXIA TION.

Effects of Overexposure:EYES: CAN CAUSE SEVERE IRRITATION, REDNESS,  
TEARING, BLURRED VISION BREATHING: EXCESSIVE INHALATION  
OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS,  
WEAKNESS, FATIGU, NAUSE A, HEADACHE, POSSIBLE UNCONSCIOUSNESS,AND  
EVEN ASPHYXIATION.SWALLOWING: NAUSEA, VOMITING, DIARRHEA, AND

PNEUMONHITIS.

## First Aid

First Aid:SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP & WATER. REMOVE CONTAMINATED CLOTH-ING BEFORE RE-USE. SEEK MEDICAL ATTENTION. EYES: FLUSH WITH LARGE AMOUNTS WATER,LIFTING UPPER/LOWER LIDS. SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM, &QUIET. BREATHED: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT GIVE SUPPLEMENTAL OXYGEN, IF NOT BREATHING GIVE CPR. KEEP WARM,QUIET,& GET MED. ATTEN

## Fire Fighting

Flash Point Method:TCC  
Flash Point:100F 37.78C  
Upper Limits:1.0  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSUREDEMAND/POSITIVE PRESSURE MODE WHEN FIGHTING FIRES. WATER SPRAY MAY BE INEFFECTIV  
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. CONTAINERS MAYEXPLODE WHEN EXPOSED TO EXTREME HEAT.KEEP IGNITION SOURCES AWAY AS VAPORS TRAVEL

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. ABSORB LIQUID WITH ABSORBENT MATERIAL AND TRANSFER TO HOOD. FOR LARGE SPILLS: WEAR PROTECTIVE EQUIP. STOP LEAK ATSOURCE. PUMP LIQUID TO SALVAGE TANK. PREVENT RUN- OFF TO SEWERS, STREAMS, OR OTHER BODIESOF WATER.

## Handling

Handling and Storage Precautions:AVOID STORING IN HIGH TEMPERATURE OR NEAR OPEN FLAME. STORE DRUM OUT OF SUN AND AWAY FROM HEAT. DRUMS SHOULD BE GROUNDED AND BONDED WHEN POURING.  
Other Precautions:AVOID BREATHING SANDING DUST. KEEP CLOSURE TIGHT AND CONTAINERS UPRIGHT TO PRE- VENT LEAKAGE. DO NOT STORE OR USE NEAR HEAT. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CON TAINERS RETAIN PRODUCT RESIDUES.

## Exposure Controls

Respiratory Protection:IF TLV OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROV-ED AIR SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL. ENGINEERING/ADMINISTRATIVE CONT ROLS SHOULD BE IMPLEMENTED TO REDUCE EXP  
Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST VENTILATION) TO MAINTAIN EXPOSURE BELOW TLV.  
Protective Gloves:RESISTANT SUCH AS NITRILE RUBBER,NEOPREN  
Eye Protection:CHEMICAL SPLASH GOGGLES,SAFETY GLASSES.  
Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.  
Work Hygienic Practices:AVOID REPEATED/PROLONGED CONTACT WITH SKIN, WASH HANDS BEFOREATING OR USING WASHROOM, SMOKE IN IN SMOKING AREAS ONLY.  
Supplemental Safety and Health  
NK

## Chemical Properties

Boiling Pt:B.P. Text:300 - 300F  
Vapor Density:HEAVIER  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:40

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:AVOID HIGH TEMPERATURES, OPEN FLAMES, AND

SPARKS.

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS SUCH AS:  
CARBON DIOXIDE, CARBON MONOXIDE, AND VARIOUS HYDROCARBONS.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, FEDERAL,  
AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.