

TT-P-24E TYPE III, GRAY 26440

MSDS Number

BHDPT

National Stock Number

8010-00-598-5154

Product Name

TT-P-24E TYPE III, GRAY 26440

Manufacturer

TRIAD PAINT AND CHEMICAL CORP

Product Identification

Product ID:TT-P-24E TYPE III, GRAY 26440 MSDS Date:07/24/1989 FSC:8010 NIIN:00-598-5154 MSDS Number: BHDPT

Responsible Party

TRIAD PAINT AND CHEMICAL CORP

810 EVERGREEN AVENUE

BROOKLYN, NY 11207

US

Emergency Phone: (718) 443-2778

Info Phone: (718) 443-2778

Cage: 33151

Contractor

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

201-437-6501 Cage: 33151

Ingredients

NO HAZARDOUS INGREDIENT

RTECS: 9999999ZZ

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure:VAPORS MIGHT BE IRRITATING TO EYES,NOSE, AND THROAT. EXCESSIVE EXPOSURE MAY RESULT IN HEADACHES, DIZZINESS, AND NAUSEA. DEFATTING OF SKIN.

First Aid

First Aid:INHAL: PROVIDE FRESH AIR AND TEST. SKIN: WASH AFFECTED AREA W/SOAP AND WATER. INGST: DO NOT INDUCE VOMITING. DRINK ONE OR TWO GLASSES OF WATER TO DILUTE. SEE A PHYSICIAN. EYES: FLUSH W/RUNNING WATE R FOR 15 MINUTES.

Fire Fighting

Flash Point Method:PMCC Flash Point:105F/41C Lower Limits:6.0



Upper Limits: 1.0

Extinguishing Media: CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR SELF CONTAINED

BREATHING APPARTUS. TO AVOID INHALATION OF SMOKE OR VAPORS. DO NOT

USE WATER.

Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT,

SPARKS, & OPEN FLAMES.

Accidental Release

Spill Release Procedures: VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PICK UP SPILL IMMEDIATELY W/INERT ABSORBENTS. SAFELY DISPOSE OF SATURATED ABSORBENTS BY IMMERS- ING IN WATER. WEAR PROTECTIVE CLOTHING DURING CLEAN UP.

Handling

Handling and Storage Precautions: AVOID OPEN FLAME AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT. Other Precautions: DO NOT TAKE INTERNALLY

Exposure Controls

Respiratory Protection: ORGANIC CANNISTER MASK OR AIR PACK IF

VENTILATION IS INADEQUATE.

Ventilation: LOCAL EXHAUST IS RECOMMENDED Protective Gloves: NEOPRENE RUBBER GLOVES Eye Protection: CHEMICAL SAFETY GOGGLES Supplemental Safety and Health

NK

Chemical Properties

Vapor Pres:100F Vapor Density: 5.0 Spec Gravity: 1.645

Evaporation Rate & Reference:.13

Solubility in Water: NEG

Appearance and Odor: GRAY COLOR LIQUID HYDROCARBON ODOR

Percent Volatiles by Volume: 37.3

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS STRONG ACIDS. Stability Condition to Avoid: WARM STORAGE AND IGNITION SOURCES Hazardous Decomposition Products: CO, CO2, SMOKE, TOXIC VAPORS, FUMES

Disposal

Waste Disposal Methods: DISPOSAL METHODS MUST COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.