

ALKYD SEMI GLOSS ENAMEL GREEN 24277 TTE508C

MSDS Number

BHDQV

National Stock Number

8010-00-616-0013

Product Name

ALKYD SEMI GLOSS ENAMEL GREEN 24277 TTE508C

Manufacturer

S L GILLMAN PAINT COMPANY

Product Identification

Product ID:ALKYD SEMI GLOSS ENAMEL GREEN 24277 TTE508C

MSDS Date:11/01/1988

FSC:8010

NIIN:00-616-0013

MSDS Number: BHDQV

Responsible Party

S.L. GILLMAN PAINT COMPANY

2250 MORELAND AVE. SE.

ATLANTA , GA 30315

US

Emergency Phone: 404-509-4400

Info Phone: 404-622-1326

Cage: 00269

Contractor

S.L. GILLMAN PAINT COMPANY

ATLANTA

404 622 1326

Cage: 00269

Ingredients

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 35-40%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ASPIRATION OF MATERIAL INTO THE LUNGS
CAN CAUSE CHEMICAL PNEUMONHITIS WHICH CAN BE FATAL.

Effects of Overexposure:EYES:CAN CAUSE SEVERE
IRRITATION,REDNESS,TEARING,BLURRED VISION. SKIN:PROLONGED OR
REPEATED CONTACT CAN CAUSE MOD. IRRITATION,DEFATTING,DERMATITIS.

INGST: GASTROINTESTINAL IRRITATION,NAUSEA,VOMITING,&

DIARRHEA.INHAL: NASAL &
RESPIRATORYIRRITATION,DIZZINESS,WKNESS,FATIGUE,NAUSEA,HDACHE,UNCONS
CIOUSNESS,POSS. ASPHYXAT

Medical Cond Aggravated by Exposure:NONE EXPECTED

First Aid

First Aid:SKIN:WASH EXPOSED AREA W/SOAP & WATER. REMOVE/LAUNDER CONTAMINATED CLTHNG BEFORE REUSE. EYES:FLUSH W/LG AMOUNTS OF WATER,LIFTING UPPER/LOWER LIDS OCCASIONALLY. INGEST: DONOT INDUCE VOMITING,KEEP PERSON WARM,QUIET, & GET MEDICAL ATTENTION.INHAL: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION.SEEK MEDICAL ATTENTION

Fire Fighting

Flash Point Method:TCC
Flash Point:105F/40.56C
Upper Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:WEAR S.C.B.A. WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES. WATER SPRAY MAY BE INEFFECTIVE.
Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR& MAY TRAVEL ALONG THE GROUND & IGNITE BY FLAMES,SPARKS,SMOKING & OTHER SOURCES.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. SML SPILLS USE FLR ABSORBENT OR OTHER ABSORBENT MATL & TRANSF TO HOOD. LG SPILLS REMOVE PERSONS NOT WEARING PROTECTIVE EQUIP.STOP SPILL AT SOURCE,DIKE AREA TO PREVENT SPREADING & PUMP LIQ INTO SALVAGE TANK.

Handling

Handling and Storage Precautions:AVOID STORING IN HIGH TEMPERATURE OR NEAR OPEN FLAME. STORE DRUM OUT OF SUN & AWAY FROM HEAT.
Other Precautions:DONOT WELD OR FLAME CUT AN EMPTY DRUM. AVOID BREATHING SANDING DUST.KEEP CLOSURE TIGHT & UPRIGHT TO PREVENT LEAKAGE. CONTAINERS OF THIS MATL MAY BE HAZARDOUS WHEN EMPTIED.CONTNR RETAINS RESIDUES,HAZARD PRECAUTIONS ON DATA SHEET MUST BE OBSERVED.

Exposure Controls

Respiratory Protection:AIR SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL.SHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS.ENGINEERING/ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:PROVIDE SUFFICIENT MECH. OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:NITRILE RUBBER,NEOPRENE,RESIST. GLOVES

Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GLASSES

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING AND BOOTS

Work Hygienic Practices:AVOID REPEATED OR PROLONGED CONTACT W/SKIN, WASH HANDS BEFORE EATING OR USING WASHROOM,SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

NK

Chemical Properties

Boiling Pt:B.P. Text:300F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:48.0

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAMES, AND SPARKS

Hazardous Decomposition Products:CARBON DIOXIDE/MONOXIDE AND VARIOUS HYDROCARBONS

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.