ALKYD SEMI GLOSS ENAMEL BLUE 25526

MSDS Number

BHDQW

National Stock Number

8010-00-616-0016

Product Name

ALKYD SEMI GLOSS ENAMEL BLUE 25526

Manufacturer

S L GILLMAN PAINT COMPANY

Product Identification

Product ID:ALKYD SEMI GLOSS ENAMEL BLUE 25526
MSDS Date:11/01/1988
FSC:8010
NIIN:00-616-0016
MSDS Number: BHDQW

Responsible Party

S.L. GILLMAN PAINT COMPANY

2250 MORELAND AVE. SE.

ATLANTA , GA 30315

US

Emergency Phone: 404-509-4400

Info Phone: 404-622-1326

Cage: OO269

Contractor

S.L. GILLMAN PAINT COMPANY

ATLANTA

404 622 1326

Cage: OO269

Ingredients

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 35-40%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL
Effects of Overexposure:EYES: CAN CAUSE SEVERE IRRI,REDNESS,TEARING,BLURRED VISION. SKIN: PROLONGED/REPEATED CONTACT CAN CAUSE MOD. IRRI,DEFATTING,DERMATITIS. INGEST: GASTROINTESTINAL IRRI,NAUSEA,VOMITING & DIARRHEA. INHAL: NASAL & RESPIRATORY IRR,DIZZINESS,WEAKNESS,FATIGUE, NAUSEA,HEADACHE, UNCONSCIOUSNESS, POSSIBLE ASPHYXIATION.
Medical Cond Aggravated by Exposure:NONE EXPECTED

First Aid

First Aid:SKIN: WASH EXPOSE AREA W/SOAP & WTR. REMOVE/LAUNDER CONTAM CLOTHING BEFORE REUSEEYES: FLUSH W/LG AMTS OF WTR, LIFTING UPPER/LOWER LIDS OCCASIONALLY. INGEST: DO NOT INDUCE VOMITING, KEEP PERSON WARM, Q UIET & GET MED ATTN. INHAL: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFF, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE CPR. SEEK MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:105 F 40.56 C
Upper Limits:1.2
Extinguishing Media:FOAM, CO2, AND DRY CHEMICAL
Fire Fighting Procedures:WEAR S.C.B.A. WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES. WATER SPRAY MAY BE INEFFECTIVE
Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR& MAY TRAVEL ALONG THE GROUND & IGNITE BY FLAMES,SPARKS,SMOKING & OTHER SOURCES

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. SML SPILLS USE FLR ABSORBENT/OTHER ABSORBENT MATERIAL/TRANSF TO HOOD. LG:REMOVE PERSON NOT WEARING PROTECTIVE EQUIPSTOP SPILL AT SOURCE, DIKE AREA TO PREVENT SPREADI NG & PUMP LIQ INTO SALVAGE TANK

Handling

Handling and Storage Precautions:AVOID STORING IN HIGH TEMPERATURE OR NEAR OPEN FLAME. STORE DRUM OUT OF SUN & AWAY FROM HEAT.
Other Precautions:DO NOT WELD OR FLAME CUT AN EMPTY DRUM. AVOID BREATHING SANDING DUST. KEEP CLOSURE TIGHT & UPRIGHT TO PREVENT LEAKAGE. CONTAINER OF THIS MATERIAL MAYBE HAZARDOUS WHEN EMPTIED. CONTAINER RESIDUE,HAZARD PRECAUSTIONS ON DATA MUST BE OBSERVED.

Exposure Controls

Respiratory Protection:AIR SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTRLOSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPERATORS UNDER SPECIFIED CONDITIONS. ENGINEERING/ADMIN CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPLOSION
Ventilation:PROVIDE SUFFICIENT MECH. OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV
Protective Gloves:NITRILE RUBBER, NEOPRENE, RESIST. GLOVES
Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GLASSES
Other Protective Equipment:WEAR IMPERVIOUS CLOTHING AND BOOTS
Work Hygienic Practices:AVOID REPEATED OR PROLONGED CONTACT W/SKIN, WASH HANDS BEFORE EATING OR USING WASHROOM, SMOKE IN SMOKING AREAS ONLY
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:300 F
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:48.0

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAMES, AND SPARKS
Hazardous Decomposition Products:CARBON DIOXIDE/MONOXIDE AND VARIOUS HYDROCARBONS

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, OR

LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.