
ALKYD SEMI GLOSS INTERIOR BLUE 25526

MSDS Number

BHDQY

National Stock Number

8010-00-616-0016

Product Name

ALKYD SEMI GLOSS INTERIOR BLUE 25526

Manufacturer

CHEMRAY COATINGS CORP

Product Identification

Product ID:ALKYD SEMI GLOSS INTERIOR BLUE 25526

MSDS Date:09/07/1989

FSC:8010

NIIN:00-616-0016

MSDS Number: BHDQY

Responsible Party

CHEMRAY COATINGS CORP

209 N. MICHIGAN AVE.

KENILWORTH , NJ 07033

US

Emergency Phone: 1-800-924-9300

Preparer: FRED ARMSTRONG

Cage: OBRN9

Contractor

CHEMRAY COATINGS CORP.

NA

KENILWORTH, NJ 07033

US

800-924-9300

Cage: OBRN9

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 29%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION

Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED
BY OVER INHALATION

First Aid

First Aid:EYE: FLUSH WITH WATER 15 MIN/UNTIL IRRI SUBSIDES. IF IRRI PERSIST CALL PHYSICIAN
SKIN: REMOVE CONTAM CLOTHING & LAUNDER WITH SOAP & WATER. INHALATION: REMOVE TO FRESH AIR, CALL PHYSICIAN.
INGESTION: DO NOT INDUCE VOMITING, CALL A PHYSICIAN

Fire Fighting

Flash Point Method:SCC
Flash Point:103 F 39.44 C
Lower Limits:0.9
Upper Limits:7
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG AND DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPOR OR FUMES
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED USE WATER SPRAY TO DISPERSE THE VAPORS FOR FIRE FIGHTERS

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA. IF LARGE: KEEP PRODUCT FROM ENTERING SEWER & WATERCOURSE BY Diking, Advise Authorities if Product Entered

Handling

Handling and Storage Precautions:AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY, WELL VENTED AREAS. AVOID DIRECT SUNLIGHT AND EXTREME TEMP. HOT OR COLD
Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF MISTS, SPRAY OR VAPORS AVOID BREATHING SANDING OR BLASTING DUST

Exposure Controls

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY IN CONFINED AREA
Ventilation:LOCAL EXHAUST-FACE VELOCITY 60FPM SPECIAL-USE ONLY WITH ADEQUATE VENTILATION MECHANICAL-EXPLOSION PROOF EQUIPMENT
Protective Gloves:CHEM-RESISTANT
Eye Protection:SPLASH GOGGLES OR FACE SHIELD
Other Protective Equipment:USE CHEM RESISTANT APRON OR CLOTHING
Supplemental Safety and Health
HAZARD CLASS-COMBUSTIBLE LIQUID

Chemical Properties

Boiling Pt:B.P. Text:308 F
Decomp Temp:Decomp Text:600 F
Vapor Pres:77 F
Vapor Density:4.8
Spec Gravity:1.34
pH:NA
Evaporation Rate & Reference:0.09
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLUE LIQUID WITH KEROSENE ODOR
Percent Volatiles by Volume:50.2
Corrosion Rate:NA

Stability

Stability Indicator/Materials to Avoid:YES
CAN REACT WITH OXIDIZING MATERIAL WHEN HEATED TO DECOMPOSITIONS
Stability Condition to Avoid:HIGH TEMPERATURE
Hazardous Decomposition Products:CARBON MONOXIDE

Disposal

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REG. DISPOSE OF ABSORBENT MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY. DISPOSE IN CONFORMITY WITH STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.