

PRIMER FOR WOOD & METAL WHITE

MSDS Number

BHDSH

National Stock Number

8010-00-664-6302

Product Name

PRIMER FOR WOOD & METAL WHITE

Manufacturer

CHEMRAY COATINGS CORP

Product Identification

Product ID:PRIMER FOR WOOD & METAL WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-6302

MSDS Number: BHDSH

Responsible Party

CHEMRAY COATINGS, CORP.

209 N. MICHIGAN AVE.

KENILWORTH , NJ 07033

US

Emergency Phone: 201-245-1111

Info Phone: 201-245-1111

Cage: OBRN9

Contractor

CHEMRAY COATINGS CORP.

NA

KENILWORTH, NJ 07033

US

800-924-9300

Cage: OBRN9

Ingredients

PIGMENTS

Fraction By Weight: 39%

VEHICLE

Fraction By Weight: 22%

MINERAL SPIRITS, RULE 66

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 39%

ACGIH TLV: 200 PPM

ADDITIVES

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES AND RESPIRATORY TRACT, MAY CAUSE HEADACHES & DIZZINESS.
PROLONG SKIN CONTACT IRRITATES.

First Aid

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MIN. OR UNTIL IRRITATION SUBSIDES. SKIN CONTACT:REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP & WATER. INHALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

Fire Fighting

Flash Point Method:SCC
Flash Point:103F 39.44C
Lower Limits:7
Upper Limits:.9
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED CONTAINERS WITH WATER SPRAY, AVOID BREATHING VAPOR OR FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA (OPEN WINDOWS, DOORS). IF LARGE SPILL, KEEP PRODUCT FROM ENTERING SEWERS AND WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED.

Exposure Controls

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY IN CONFINED AREA.
Ventilation:LOCAL/MECHANICAL EXHAUST
Protective Gloves:CHEM-RESISTANT GLOVES
Eye Protection:SPLASH GOGGLES OR FACE SHIELD
Other Protective Equipment:USE CHEM, RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEAT-ED SKIN CONTACT.
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:308F
Vapor Pres:25C Vapor Density:4.8
Spec Gravity:1.234
Evaporation Rate & Reference:.09
Solubility in Water:NEG
Percent Volatiles by Volume:61

Stability

Stability Indicator/Materials to Avoid:YES
CAN REACT WITH OXYDIZING MATERIALS WHEN HEATED TO DECOMPOSITION.
Stability Condition to Avoid:HIGH TEMPERATURES OR HEATING
Hazardous Decomposition Products:CARBON MONOXIDE

Disposal

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.