

WHITE ODORLESS ALKYD FLAT C37875

MSDS Number

BHDSJ

National Stock Number

8010-00-664-7041

Product Name

WHITE ODORLESS ALKYD FLAT C37875

Manufacturer

EVERSEAL MANUFACTURING CO INC

Product Identification

Product ID:WHITE ODORLESS ALKYD FLAT C37875

MSDS Date:05/19/1987

FSC:8010

NIIN:00-664-7041

MSDS Number: BHDSJ

Responsible Party

EVERSEAL MANUFACTURING CO., INC.

475 BROAD AVENUE

RIDGEFIELD , NJ 07657

US

Emergency Phone: 201-943-4986

Cage: EO432

Contractor

EVERSEAL MFG CO INC

RIDGEFIELD, NJ 07657-2329

US

201-943-4986

Cage: 72988

Ingredients

RESIN

Fraction By Weight: 12%

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 14%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN

CAS: 61790-53-2

RTECS: HL8600000

Fraction By Weight: 3%

OSHA PEL20 MPPCF

ACGIH TLV: 10 MG/M3 TDUST; 9293

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 18%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

ALUMINUM SILICATE

CAS: 1332-58-7

Fraction By Weight: 11%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 9%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

ODORLESS MINERAL SPIRITS

CAS: 64741-65-7

Fraction By Weight: 32%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:INHALATION MAY CAUSE DIZZINESS, NAUSEA OR IN
EXTREME CASES, UNCONSCIOUSNESS. MAYBE MODERATELY IRRITATING TO SKIN
AND EYES.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE
VOMITING. CALL A PHYSICIAN. UNCONSCIOUSNESS: CALL PHYSICIAN.
EFFECT: OXYGEN RESUSCITATION. SKIN: SOAP & WATER. EYES: FLUSH WITH
WATER. CA LL PHYSICIAN.

Fire Fighting

Flash Point:123F

Upper Limits:1

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING MEDIUM

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES. ENSURE ADEQUATE
VENTILA- TION. ABSORB ON DRY ABSORPTION MATERIAL. USE SPARKPROOF
SCOOP FOR LARGE SPILLS.

Handling

Handling and Storage Precautions:KEEP AWAY FROM IGNITION SOURCES.

Exposure Controls

Respiratory Protection:IN POORLY VENTILATED AREAS, USE CANISTER FUME MASK.

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED.

Eye Protection:GOGGLES

Supplemental Safety and Health

NK

Chemical Properties

Boiling Pt:B.P. Text:346 - 403F

Vapor Density:HEAVIER

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:57

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON MONOXIDE OR CARBON DIOXIDE

Disposal

Waste Disposal Methods:AS PER LOCAL REGULATIONS FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.