

TT-P-32B TY I BLACK 37038

MSDS Number

BHDSM

National Stock Number

8010-00-664-7078

Product Name

TT-P-32B TY I BLACK 37038

Manufacturer

TRIAD PAINT AND CHEMICAL CORP

Product Identification

Product ID:TT-P-32B TY I BLACK 37038

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-7078

MSDS Number: BHDSM

Responsible Party

TRIAD PAINT AND CHEMICAL CORP

810 EVERGREEN AVENUE

BROOKLYN , NY 11207

US

Emergency Phone: (718) 443-2778

Info Phone: (718) 443-2778

Cage: 33151

Contractor

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

201-437-6501

Cage: 33151

Ingredients

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 44.8%

ACGIH TLV: 100 PPM

SOLVENT

Fraction By Weight: 44.8%

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:VAPORS MIGHT BE IRRITANT TO EYES, NOSE & THROAT.
EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS & NAUSEA.

DEFATTING TO SKIN.

First Aid

First Aid:INHALATION: PROVIDE FRESH AIR & REST. SKIN: WASH AFFECTED AREA WITH SOAP & WATERINGESTION: DO NOT INDUCE VOMITING. DRINK ONE OR TWO GLASSES OF WATER TO DILUTE SEE A PHYSICIAN. EYES: FLUSH WITH COOL R UNNING WATER FOR AT LEAST 15 MIN.

Fire Fighting

Flash Point Method:PMCC
Flash Point:105 F 41 C
Lower Limits:7.0
Upper Limits:1.0
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS DO NOT USE WATER
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELECTRICAL EQUIP, SPARKS, & OPEN FLAMES. VAPORS FORM EXPLOSIVE MIXTURE BETWEEN UPPER & LOWER EXPLOSIVE UNTIS

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PICK UP SPILL IMMEDIATELY WITH INERT ABSORBENT(S) & NON SPARKING TOOLS. SAFELY DISPOSE OF SATURATED ABSORBENT BY IMMERSING IN WATER. WEAR PROTECTIVE CLO THING DURING CLEAN UP

Handling

Handling and Storage Precautions:AVOID OPEN FLAME & SPARK SOURCES. PROVIDE ADEQUATEVENTILATION. AVOID EXCESSIVE HEAT.
Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED/REPEATED CONTACT WITH SKIN. AND AVOID PROLONGED/REPEATED BREATHING OF VAPORS

Exposure Controls

Respiratory Protection:ORGANIC CANISTER MASK OR AIR PACK IF VENTILATION IS INADEQUATE
Ventilation:LOCAL IS RECOMMENDED AND MECHANICAL WITH APPROVED CLASS D EXPLOSION PROOF MOTOR AND SWITCHES
Protective Gloves:NEOPRENE RUBBER GLOVES
Eye Protection:CHEMICAL SAFETY GOGGLES
Other Protective Equipment:PROTECTIVE CLOTHING
Work Hygienic Practices:GOOD GENERAL HYGIENE PRACTICES
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:316-388 F
Vapor Pres:100F 4.75
Vapor Density:4.8 AIR
Spec Gravity:1.084
Evaporation Rate & Reference:.15
Solubility in Water:NEG
Appearance and Odor:BLACK COLORED LIQUID. HYDROCARBON ODOR
Percent Volatiles by Volume:61.98

Stability

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES
Stability Condition to Avoid:WARM STORAGE AND IGNITION SOURCES
Hazardous Decomposition Products:CO, CO2, SMOKE, TOXIC VAPORS AND FUMES

Disposal

Waste Disposal Methods:DISPOSAL METHODS MUST COMPLY WITH ALL LOCAL, STATEAND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.