

## **PAINT READY MIXED**

### **MSDS Number**

BHDST

### **National Stock Number**

8010-00-664-9077

### **Product Name**

PAINT READY MIXED

### **Manufacturer**

SHIPSHAPE MAINT CO INC

### **Product Identification**

Product ID:PAINT READY MIXED

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-9077

MSDS Number: BHDST

### **Responsible Party**

SHIPSHAPE MAINT. CO. INC.

2254 75TH PLACE NE.E.

WASHINGTON D.C. , DC 20018

US

Emergency Phone: 202-526-3100

Info Phone: 202-526-3100

Cage: SHIPS

### **Contractor**

SHIPSHAPE MAINT. CO. INC.

WASHINGTON D.C., DC 20018

US

202-526-3100

Cage: SHIPS

### **Ingredients**

SOLVENTS

Fraction By Weight: 45.297%

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:INHALATION OF HIGH CONCENTRATIONS MAY HAVE RESULTS FROM MILD DEPRESSION TO CONVULSIONS OR LOSS OF CONSCIOUSNESSS

### **First Aid**

First Aid:IF OVERCOMED BY VAPOR, REMOVE FROM EXPOSURE IMMEDIATELY AND CALL A PHYSICIAN. IF BREATHING IS IRREGULAR OR STOPPED, START RESUSCITATION IMMEDIATELY AND ADMINISTER OXYGEN. REMOVE CONTAMINATED CLOTHING AND WASH SKIN. FLUSH EYES WITH COLD WATER

### **Fire Fighting**

Flash Point Method:TCC

Flash Point:113 F 45 C

Lower Limits:6.5  
Upper Limits:1.0  
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG  
Fire Fighting Procedures:USE AIR SUPPLIED EQUIPMENT FOR RESCUE IN  
ENCLOSED AREAS  
Unusual Fire/Explosion Hazard:HYDROCARBONS - FORM EXPOSIVE MIXTURE WITH  
AIR

## Accidental Release

Spill Release Procedures:AVOID OPEN FLAMES: SPARKS SOURCES: PROVIDE  
ADEQUATE VENTILATION

## Handling

Handling and Storage Precautions:AVOID OPEN FLAMES, SPARK SOURCES AND  
HIGH TEMPERATURE AREAS

## Exposure Controls

Respiratory Protection:HYDROCARBON VAPOR CANISTER; AIR SUPPLIES OR HOSE  
MASK  
Ventilation:LOCAL; FACE VELOCITY > 60 FPM. MECHANICAL; EXPLOSION-PROOF  
VENTILATION EQUIPMENT  
Protective Gloves:HYDROCARBON-INSOLUBLE RUBBER/PLASTIC  
Eye Protection:CHEM GOGGLES/ FACE SPLASH SHIELD  
Other Protective Equipment:HYDROCARBON-INSOLUBLE APRON  
Supplemental Safety and Health  
NK

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:318-345 F  
Vapor Pres:< 1MM  
Vapor Density:4.3  
Spec Gravity:0.8762  
Evaporation Rate & Reference:0.08  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:WATER CLEAR COLOR - AROMATIC HYDROCARBON ODOR  
Percent Volatiles by Volume:100

## Stability

Stability Indicator/Materials to Avoid:YES  
OXYGEN & OXIDANTS: WILL DISSOLVE SOME PLASTICS AND RUBBER  
Stability Condition to Avoid:MAY IGNITE AT TEMPERATURES ABOVE 700 F  
Hazardous Decomposition Products:INCOMPLETE COMBUSTION PRODUCES CARBON  
MONOXIDE

## Disposal

Waste Disposal Methods:CLEAN AREA WITH RAGS IMMED: REMOVE PAINT STAINS  
WITH AROMATIC SOLVENT: STORE SOILED RAGS IN CLOSED METAL CONTAINER  
TO PREVENT INTAKE OF OXYGEN RESULTING IN POSSIBLE SPONTANEOUS  
COMBUSTION

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.