

## **PAINT READY MIXED**

### **MSDS Number**

BHDSV

### **National Stock Number**

8010-00-664-9077

### **Product Name**

PAINT READY MIXED

### **Manufacturer**

NELSON TECHNICAL COATINGS INC

### **Product Identification**

Product ID: PAINT READY MIXED

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00-664-9077

MSDS Number: BHDSV

### **Responsible Party**

NELSON TECHNICAL COATINGS INC

2147 N TYLER AVE

SOUTH EL MONTE , CA 91733-2754

US

Emergency Phone: 213-575-3333

Info Phone: 213-575-3333

Cage: 60800

### **Contractor**

NELSON TECHNICAL COATINGS INC

SOUTH EL MONTE, CA 91733-2754

US

Cage: 60800

### **Ingredients**

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 14 - 21%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 49%

OSHA PEL100 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5 - 10%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

## First Aid

First Aid:FUMES: REMOVE TO FRESH AIR. RESTORE BREATHING KEEP WARM & QUIET. CALL PHYSICIAN.SPLASH EYE: FLUSH WITH LARGE QUANTITIES OF RUNNING WATER FOR 15 MIN. SEEK MEDICAL HELP. SKIN: WASH WELL WITH RUNNING WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN.

## Fire Fighting

Flash Point Method:SCC

Flash Point:86F/30.00C

Lower Limits:1.2

Upper Limits:1.0

Extinguishing Media:NFP CLASS B, EXTINGUISHERS,CO21, DRY CHEMICAL, OR FOAM DESIGNED TO EXTINGUISH NFPA CL I LIQUID FIRES

Fire Fighting Procedures:WTR SPRAY MAY BE INEFFECT, WTR MAY BE USED TO COOL CONTAINER TO PREVENT PRESSUREBUILD UP & POSSIBLE EXPLOSION WHEN EXPOSED TO EXTREME HEAT. USE FOG NOZZLES

Unusual Fire/Explosion Hazard:PRESSURE MAY BUILD UP WHEN CLOSED CONTAINER IS EXPOSED TO HEAT. DO NOT APPLY TO HOT SURFACE. PAINT VAPORS MAY CAUSE VIOLENT EXPLOSION. USE EXPLOSION PROOF EQUIP

## Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL OR STATIC, OR FRICTIONAL SPARKS). AVOIDBREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

## Handling

Handling and Storage Precautions:DO NOT STORE OVER 120 F. STORE LARGE QUANTITIES INBLDS DESIGNED & PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS

Other Precautions:DO NOT TAKE INTERNALLY

## Exposure Controls

Respiratory Protection:BUREAU OF MINES APPROVED CHEMICAL-MECHANICAL FILTERS TO REMOVE PARTICALS, GAS, AND VAPOR

Ventilation:LOCAL-TO KEEP TLV/LEL OF MOST HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMIT

Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT

Eye Protection:GOGGLES OR FACE SHIELDS

Other Protective Equipment:IN CONFINED AREAS USE BUREAU OF MINES APPROVED AIRLINE TYPE RESPIRATORS OR HOODS

Supplemental Safety and Health

NK

## Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:232-308 F

Vapor Density: > AIR  
Spec Gravity: 1.128  
Evaporation Rate & Reference: SLOWER THAN ETHER  
Percent Volatiles by Volume: 70

## Stability

Stability Indicator/Materials to Avoid: YES  
WATER  
Stability Condition to Avoid: FLAME AND HIGH HEAT  
Hazardous Decomposition Products: NORMALLY CARBON COMBUSTION PRODUCTS

## Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, &  
FEDERAL REG. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE  
CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.