

CARBON DIOXIDE SOLID

MSDS Number

BHDSZ

National Stock Number

6830-00-682-6841

Product Name

CARBON DIOXIDE SOLID

Manufacturer

HELLER'S CARBONIC WEST INC

Product Identification

Product ID: CARBON DIOXIDE SOLID

MSDS Date: 07/25/1986

FSC: 6830

NIIN: 00-682-6841

MSDS Number: BHDSZ

Responsible Party

HELLER'S CARBONIC WEST, INC.

1902 MARVEL STREET

WEBSTER, IA 50595

US

Emergency Phone: CHEMTREC 800-424-9300

Info Phone: 515-832-6270

Cage: LO803

Contractor

MOTOROLA INC GOVERNMENT ELECTRONICS DIVISION

HUNTSVILLE, AL 35801-5335

US

515-832-6270

Cage: 5D595

Ingredients

CARBON DIOXIDE

CAS: 124-38-9

RTECS: FF6400000

Fraction By Weight: 99.5%

OSHA PEL5000 PPM

ACGIH TLV: 5000PPM/30000STEL;93

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: AT 2-3% CONCENTRATION, SYMPTOMS OF SIMPLE ASPHYXIA OCCUR; 3-5% CAUSES INCREASED RESPIRATION & HEADACHE. HIGHER CONCENTRATIONS CIRCULATORY INSUFFICIENCY LEADING TO COMA & DEATH. CO₂ IS THE MOST POWERFUL CEREBRAL VASODILATOR KNOWN. SOLID CARBON DIOXIDE, WHEN TOUCHED, CAN CAUSE SEVERE FROSTBITE, SIMILAR TO A BURN.

Effects of Overexposure: RAPID BREATHING, IRRITATED NOSE & THROAT, &

WATERY EYES CAUSED BY THE FORMATION OF CARBONIC ACID, A VERY WEAK ACID.

Medical Cond Aggravated by Exposure:PRE-EXISTING CHRONIC RESPIRATORY DISEASES OR HEARTDISEASES SHOULD REFRAIN FROM BREATHING EXCESSIVE CARBON DIOXIDE.

First Aid

First Aid:CONSCIOUS/UNCONSCIOUS ASSIST TO FRESH AIR.IF NECESSARY GIVE ASSISTED RESUSCITATION & ADMINISTERED OXYGEN.FROSTBITE SHOULD BE TREATED AS A BURN W/PROMPT MEDICAL ATTENTION.RESCUE PERSONNEL SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS W/FULLFACE MASK & HEAVY PROTECTIVE CLOTHING TO PREVENT FROSTBITE.

Fire Fighting

Flash Point:NA

Lower Limits:NON

Upper Limits:NON

Extinguishing Media:NON-FLAMMABLE,INERT GAS.USED AS AN EXTINGUISHING AGENT FOR SMOTHERING CLASS B & C FIRES.

Fire Fighting Procedures:NA

Unusual Fire/Explosion Hazard:DO NOT PLACE SOLID CO2 IN SEALED CNTS,EXCEPT FOR CNTS SPECIFICALLY DESIGNED FOR THAT PURPOSE(IE,DRY ICE CONVERTORS).CONTAINERS CAN RUPTURE & EXPLODE.

Accidental Release

Spill Release Procedures:THE AREA SHOULD BE VENTILATED.SPECIAL PRECAUTION SHOULD BE USED IN LOW AREAS NEAR SPILL WHERE HEAVIER THAN AIR CO2 MAY ACCUMULATE.CLEAN UP PERSONNEL SHOULD WEAR SCBA W/FULL FACE MASK & HEAVY PROTECTIVE CLOTHING TO PREVENT FROSTBITE.

Handling

Handling and Storage Precautions:STORE DRY ICE & DRY ICE CNTS IN COOL,WELL VENT AREA.DO NOT STORE IN CLOSED,CONFINED AREA.WHEN HANDLING DRY ICE USE HVY GLOVES,CLOTHING & FACE SHIELD.

Other Precautions:WHEN TRANSPORTING IN A VEHICLE,PROVIDE PLENTY OF VENTILATION FOR PERSONNEL IN THE VEHICLE.WHEN TRANSPORTING BY AIRPLANE,LABEL CNT & ADVISE PERSONNEL THAT DRY ICE IS BEING SHIPPED & QTY.DO NOT PUT HEAD OR BODY IN DRY ICE CONTAINERS.

Exposure Controls

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS W/FULL FACE MASK WHEN CONCENTRATIONS ARE ABOVE TLV.

Ventilation:YES LOCAL EXHAUST.

Protective Gloves:YES

Eye Protection:SAFETY GLASSES OR FULL FACE SHIELD

Other Protective Equipment:CARBON DIOXIDE PORTABLE ANALYZER.

Work Hygienic Practices:DO NOT USE DRY ICE CONTAINERS FOR ANY USE OTHER THAN TO STORE DRY ICE.KEEP DRY ICE CONTAINERS CLEAN.

Supplemental Safety and Health

NK

Chemical Properties

HCC:G3

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:-69.88F

Vapor Pres:68F831PSIG

Vapor Density:@68F 1.53

Spec Gravity:@2F 1.014

Evaporation Rate & Reference:NA

Solubility in Water:@68F 87.8% BY VOL

Appearance and Odor:COLORLESS, SLIGHT PUNGENT ODOR. MELT PT

CONT:@75.13 PSIA

Stability

Stability Indicator/Materials to Avoid:YES

CARBON DIOXIDE WILL REACT W/ALKALINE MATERIALS TO FORM CARBONATES & BICARBONATES.EXPLOSION CAN OCCUR W/REACTIVE METALS.

Stability Condition to Avoid: CARBON DIOXIDE IS STABLE UNDER NORMAL CONDITIONS OF USE & STORAGE.
Hazardous Decomposition Products: CARBON DIOXIDE CAN DECOMPOSE TO CARBON MONOXIDE & OXYGEN ABOVE 3000F.
Conditions to Avoid Polymerization: CARBON DIOXIDE CAN CAUSE VIOLENT POLYMERIZATION OF ACRYLALDEHYDE OR ETHYLENEIMINE.

Disposal

Waste Disposal Methods: PLACE IN WASTE CONTAINER W/OPEN OR LOOSELY CLOSED TOP. PLACE CONTAINER IN WELL VENTILATED AREA THAT IS NOT ACCESSABLE TO UNAUTHORIZED PERSONNEL. ALLOW DRY ICE TO SUBLIME NATURALLY TO CO₂ VAPOR. DO NOT USE HEAT OR WATER TO INCREASE SUBLIMATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.