

LIQUID POLISH

MSDS Number

BHDTF

National Stock Number

7930-00-721-8873

Product Name

LIQUID POLISH

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID: LIQUID POLISH

MSDS Date: 05/01/1987

FSC: 7930

NIIN: 00-721-8873

MSDS Number: BHDTF

Responsible Party

INDUSTRIAL FLOOR FINISHES

605 SPRING STREET

BEDFORD , MA 01730

US

Emergency Phone: (617) 667-5161

Preparer: T. PITROL FFYO

Cage: INDUS

Contractor

PEMATEX INDUSTRIAL CORPORATION

AVON, CT 06001

US

1-617-667-5161

Cage: PERMA

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8924000

Fraction By Weight: 17%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: PRIMARY EYE/SKIN IRRITANT WITH CONTACT. INHALATION: HEADACHE, DIZZINESS & NAUSEA CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV

Effects of Overexposure: NK

PRIMARY EYE/SKIN IRRITANT WITH CONTACT. INHALATION: HEADACHE, DIZZINESS & NAUSEA CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV

First Aid

First Aid:EYE CONTACT: FLUSH WITH WATER, SKIN: WASH WITH SOAP & WATER, APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING, CALL PHYSICIAN. INGESTION: DRINK WATER OR MILK, DO NOT INDUCE VOMIT ING. CALL POISON CONTROL

Fire Fighting

Flash Point Method:TCC
Flash Point:MIN 104F 40.00C
Lower Limits:0.8
Upper Limits:6.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION, SPRINKLE WITH ABSORB- ENT. FOG WITH WATER FLUSH/SCRAPE INTO RETAINING AREA/CONTAINER. INCREASE VENTILATION AVOID BREATH-ING VAPORS.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME, USE AD- EQUATE VENTILATION AVOID PROLONGED/REPEATED CONTACT KEEP CONTAINER CLOSED
Other Precautions:KEEP AWAY FROM CHILDREN
AVOID STATIC BUILD UP

Exposure Controls

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV
Ventilation:LOCAL: YES, MECHANICAL: EXHAUST FROM LOWER LEVELS
Protective Gloves:USE RUBBER GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM
Supplemental Safety and Health
NK

Chemical Properties

Boiling Pt:B.P. Text:215
Vapor Pres:2
Vapor Density:3.8
Spec Gravity:1.1
Evaporation Rate & Reference:0.8 WATER
Solubility in Water:PARTIAL
Appearance and Odor:GREEN CREAMY LIQUID
Percent Volatiles by Volume:74

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME AND FIRE
Hazardous Decomposition Products:THERMAL DECOMPOSTION PRODUCES FUMES
MAY YIELD CARBON MON- OXIDE

Disposal

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN ACCORDANCE WITH LOCAL STATE & FEDERAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN FUMES. DO NOT EXPOSE TO HEAT OR FLAME

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.