

## **AEROSOL SPRAY PAINT BLUE 25184**

### **MSDS Number**

BHDT5

### **National Stock Number**

8010-00-721-9753

### **Product Name**

AEROSOL SPRAY PAINT BLUE 25184

### **Manufacturer**

NATIONAL AEROSOL PRODUCTS CO

### **Product Identification**

Product ID:AEROSOL SPRAY PAINT BLUE 25184

MSDS Date:11/02/1987

FSC:8010

NIIN:00-721-9753

MSDS Number: BHDT5

### **Responsible Party**

NATIONAL AEROSOL PRODUCTS CO.

2193 E. 14TH STREET

LOS ANGELES , CA 90021

US

Emergency Phone: 213-527-2668

Cage: 59986

### **Contractor**

NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

LOS ANGELES, CA 90021-2843

US

Cage: 59986

### **Ingredients**

VINYL TOLUENE ALKYD

CAS: 25013-15-4

ACGIH TLV: ND

### **PIGMENTS**

150-BUTYL ACETATE

CAS: 123-86-4

ACGIH TLV: 150 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ALIPHATIC HYDROCARBONS

CAS: 64742-89-8

ACGIH TLV: 400PPM

CHLORINATED HYDROCARBONS

CAS: 75-09-2

ACGIH TLV: 200PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIA NT; 9192

## Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Effects of Overexposure: EYES: IRRITATION

SKIN: MINOR IRRITATION

INHALATION: DIZZINESS INGESTION: NAUSEA

## First Aid

First Aid: EYES: FLUSH W/ WATER MINIMUM OF FIVE MINUTES.

SKIN: WASH W/ WATER

INHALATION: REMOVE TO FRESH AIR. CALL

PHYSICIAN. GIVE MOUTH-TO-MOUTH RESUSCITATION IF BREATHING STOPS.

INGESTION: GET MEDICAL HELP

## Fire Fighting

Flash Point: BELOW 25F

Extinguishing Media: WATER FOG, STANDARD FOAM, CO2, DRY CHEMICAL, HALON

Fire Fighting Procedures: KEEP CONTAINERS COOL. USE EQUIP./SHIELDING TO

PROTECT PERSONNEL AGAINST BURSTING/VENTING CONTAINERS. DO NOT

PUNCTURE/INCINERATE CONTAINER. BURSTING/VENTING W/ TEMPS OVER 120F

Unusual Fire/Explosion Hazard: DO NOT USE NEAR OPEN FLAME, FIRE OR WHILE SMOKING.

## Accidental Release

Spill Release Procedures: MOP UP, SOAK UP, OR WIPE UP IMMEDIATELY. PROVIDE VENTILATION.

## Handling

Handling and Storage Precautions: DO NOT STORE WHERE TEMPERATURE COULD EXCEED 120F

Other Precautions: USE AND FOLLOW LABEL DIRECTIONS.

## Exposure Controls

Ventilation: RECOMMENDED/LOCAL EXHAUST ADEQUATE

Work Hygienic Practices: WASH WITH WATER

Supplemental Safety and Health

NK

## Chemical Properties

HCC: V3

Vapor Pres: 40-50

Spec Gravity: 0.976

Solubility in Water: SLIGHT

Appearance and Odor: PAINT/SOLVENT ODOR

## Stability

NK  
Stability Condition to Avoid:DO NOT STORE ABOVE 120F.

## Disposal

Waste Disposal Methods:DO NOT PUNCTURE OR INCINERATE "EMPTY" OR FULL CANS.ONCE SPILLS OR LEAKS ARE CLEANED UP,DISPOSE OF WASTE IN ACCORDANCE WITH GOVERNMENTAL ORDINANCES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.