

ACRYLIC LATEX PAINT EXTERIOR WHITE 37875

MSDS Number

BHDWR

National Stock Number

8010-00-823-7962

Product Name

ACRYLIC LATEX PAINT EXTERIOR WHITE 37875

Manufacturer

ASAHIPEN AMERICAN INC

Product Identification

Product ID:ACRYLIC LATEX PAINT EXTERIOR WHITE 37875

MSDS Date:02/01/1989

FSC:8010

NIIN:00-823-7962

MSDS Number: BHDWR

Responsible Party

ASAHIPEN AMERICAN INC.

1126 SW SPOKANE STREET

SEATTLE , WA 98134-1197

US

Emergency Phone: 303-573-1014 POISON CENTER

Info Phone: 206-682-4603

Preparer: DOUGLAS KIER

Cage: DO047

Contractor

ASAHIPEN AMERICA INC.

SEATTLE, WA 98134-1197

303-573-1014 POISON CENTER

Cage: DO047

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:ADVERSE HEALTH EFFECTS FROM VAPORS OR SPRAY
MISTS IN POORLY VENTILATED AREAS MAYINCLUDE IRRITATION OF THE
MUCOUS MEMBRANES OF THE NOSE,THROAT & RESPIRATORY TRACT & SYMPTOMS
OF HEADACHE & NAUSEA.PROLONGED OR REPEATED EXPOSURE TO PRODUCT

MAYCAUSE SKIN ITTITATION.DIRECT CONTACT W/PRODUCT MAY RESULT IN EYE IRRITATION.

First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR.EYE & SKIN:PROMPTLY & THOROUGHLY WASH EYES W/WTR FOR AT LEAST 15 MINS & CONSULT A DOCTOR IF IRRITATION PERSISTS.REMOVE CONTAMINATED CLOTHING BEFORE REUSE.INGESTION:IF VIC TIM IS CONSCIOUS,GIVE TWO GLASSES OF WATER TO DRINK & CALL A PHYSICIAN.DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Fire Fighting

Flash Point:NONE

Upper Limits:NA

Extinguishing Media:THE PAINT WILL NOT BURN UNTIL WTR HAS EVAPORATED.FOR RESIDUAL SOLIDS USE:FOAM,ALCOHOL FOAM,CO2,DRY CHEMICAL OR WTR FOG.

Fire Fighting Procedures:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.WTR MAY BE USED TO COOL UNRUPTURED CONTAINERS.AVOID SPREADING BURNING LIQ W/WTR USED FOR COOLING PURP

Unusual Fire/Explosion Hazard:THE MATERIAL CAN SPLATTER IF TEMP EXCEEDS BOILING POINT.THE RESIDUAL SOLIDS ARE CAPABLE OF BURNING,GIVING OFF CARBON MONOXIDE & CARBON DIOXIDE, ETC.

Accidental Release

Spill Release Procedures:RECOVER FREE LIQ.PICK UP REMAINING LIQ W/ABSORBANTMATERIAL &PLACE INTO CONTAINER FOR DISPOSAL.WASH AREA W/WTR & DETERGENT.DO NOT WASH INTO PUBLIC WTRSOURCE.

Handling

Handling and Storage Precautions:PRODUCT SHOULD BE STORED AT ROOM TEMP TO PROLONG LIFE.KEEP FROM FREEZING SO PRODUCT DOES NOT COAGULATE.DO NOT APPLY WHEN TEMP IS BELOW 50F/10C.

Other Precautions:DO NOT TAKE INTERNALLY.AVOID PROLONGED CONTACT W/SKIN OR BREATHING OF SPRAY MISTCLOSE CONTAINER AFTER EACH USE.KEEP AWAY FROM CHILDREN.THESE PRODUCTS CONTAIN NOLEAD PIGMENTS.

Exposure Controls

Respiratory Protection:USE ORGANIC VAPOR CANISTER OR SUPPLIED-AIR RESPIRATORY PROTECTION WHEN TLV IS EXCEEDED.

Ventilation:ALL APPLICATION AREAS SHOULD BE PROVIDED W/SUFFICIENT MECHANICAL VENT W/EXPLOSION PROOF EQUIP TO MAINTAIN EXPO LEVELProtective Gloves:IMPERMEABLE

Eye Protection:FFSPLASH GOGGLES OR FACE SHIELD

Work Hygienic Practices:USE PROTECTIVE CREAM WHERE SKIN CONTACT IS LIKELY.WEAR IMPERVIOUS CLOTHING & BOOTS.WASH HANDS BEFORE EATING.

Supplemental Safety and Health

WORK HYGIENE: SMOKE IN SMOKING AREA ONLY.

Chemical Properties

Boiling Pt:B.P. Text:212F 100C

Vapor Density:< AIR

pH:8.5

Viscosity:80-100KU

Evaporation Rate & Reference:< ETHER

Solubility in Water:COMPLETE

Appearance and Odor:THICK LIQUID, WHITE & VARIOUS COLORS, SLIGHT AMMONIA ODOR

Percent Volatiles by Volume:59.5

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH TEMPERATURE

Hazardous Decomposition Products:WHEN PRODUCT IS HEATED TO DECOMPOSITION IT MAY PRODUCE FUMESWHICH CONTAIN CABON MONOXIDE & CARBON DIOXIDE, ETC.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL,STATE & LOCAL REGULATIONS.BEFORE ATTEMPTING CLEAN UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SELECTIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.