

# **SILICON RUBBER SEALANT ID RTV103**

## **MSDS Number**

**BHDXF** 

### **National Stock Number**

8010-00-851-0211

## **Product Name**

SILICON RUBBER SEALANT ID RTV103

#### Manufacturer

GENERAL ELECTRIC CO SILICONE PRODUCTS DIV

## **Product Identification**

Product ID:SILICON RUBBER SEALANT ID RTV103 MSDS Date:10/21/1985 FSC:8010 NIIN:00-851-0211

MSDS Number: BHDXF

# **Responsible Party**

GENERAL ELECTRIC CO., SILICONE PRODUCTS DIV.

WATERFORD, NY 12188

US

Emergency Phone: 518-237-3330 (24 HOURS)

Info Phone: 518-237-3330 (24 HOURS)

Preparer: DA POLSINELLI

Cage: OD426 Contractor

MULTI-AMP CORP

24552

DALLAS, TX 75237-1019

US

518-237-3330

Cage: 00426

**Ingredients** 

CAS: 4253-34-3

# **METHYLTRIACETOXYSILANE**

Fraction By Weight: OSHA PEL10 PPM ACGIH TLV: 10 PPM

#### **Hazards**

LD50 LC50 Mixture: ACUTE ORAL LD50: 2060 (RAT) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:INGESTION:MAY CAUSE GASTRIC DISTRESS.INHALATION: CAUSES MODERATE RESPIRATORY IRRITATION. Effects of Overexposure: IHALATION: IRRITATION OF THE MOUTH, NOSE, & THROAT. IRRITATES EYES, LIPS, GUMS, TONGUE, & SKIN. Medical Cond Aggravated by Exposure: RESPIRATORY, DERMAL AILMENTS.

#### First Aid



First Aid:INGESTION:RINSE MOUTH W/WTR SEVERAL TIMES.SKIN:TO CLEAN FROM SKIN, REMOVE COMPLETELY W/A DRY CLOTH OR PAPER TOWEL, BEFORE WASHING W/DETERGENT &WTR.GET MEDICAL ATTN IS IRRITATION PERSISTS.INHALATION:MOS E PERSON TO FRESH AIR.EYES:IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES W/PLENTY OF WTR FOR AT LEAST 15 MINS & GET MEDICAL ATTN IF IRRITATION PERSISTS.

## Fire Fighting

Flash Point:NA

Extinguishing Media: ALL STANDARD FIREFIGHTING MEDIA.

Fire Fighting Procedures: NONE KNOWN.

#### **Accidental Release**

Spill Release Procedures: WIPE OR SOAK UP IN AN INERT MATERIAL & PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACE W/DETERGENT & WTR TO REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE EQUIP AS SPECIFIED IN THE PROTECTIVE EQUI P SECTION.

## Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE.AVOID CONTACT W/SKIN & EYES.WEARERS OF CONTACTS MUST NOT TOUCHLENSES UNTIL SEALANT HAS BEEN CLEANED FROM HANDS. Other Precautions: EYE WASH STATIONS.

## **Exposure Controls**

Respiratory Protection: USE IN WELL VENTILATED AREA. Ventilation: USE ONLY IN WELL VENTILATED AREA.

Protective Gloves: CLOTH GLOVES.

Protective Gloves:CLOTH GLOVES Eye Protection:SAFETY GLASSES

Other Protective Equipment: NONE KNOWN

Supplemental Safety and Health

NK

### **Chemical Properties**

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA Vapor Pres:20C

Spec Gravity:1.02
Evaporation Rate & Reference:NEGL

Solubility in Water: 20C

Appearance and Odor: BLACK IN COLOR, ACETIC ACID ODOR.

Percent Volatiles by Volume:

## Stability

Stability Indicator/Materials to Avoid:YES NONE KNOWN

Hazardous Decomposition Products: SILICON DIOXIDE, ACETIC ACID

# **Disposal**

Waste Disposal Methods: DISPOSAL SHOULD BE MADE IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.