

CLEANING COMPOUND, SOLVENT P-C-444B TYPE I

MSDS Number

BHFBD

National Stock Number

6850-00-965-2331

Product Name

CLEANING COMPOUND, SOLVENT P-C-444B TYPE I

Manufacturer

OCTAGON PROCESS INC

Product Identification

Product ID:CLEANING COMPOUND, SOLVENT P-C-444B TYPE I

MSDS Date:07/19/1988

FSC:6850

NIIN:00-965-2331

MSDS Number: BHFBD

Responsible Party

OCTAGON PROCESS INC.

596 RIVER ROAD

EDGEWATER , NJ 07020

US

Emergency Phone: 201-945-9400

Info Phone: 201-945-9400

Cage: 82925

Contractor

OCTAGON PROCESS INC.

EDGEWATER, NJ 07020

US

201-945-9400

Cage: 82925

Ingredients

PETROLEUM DISTILLATE

CAS: 65996-93-2

Fraction By Weight: 90%

OSHA PELNA

ACGIH TLV: NA

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:IRRITATION TO SKIN, EYES, MUCOUS MEMBRANES. HIGH VAPOR CONCENTRATION CAN CAUSE CNS DEPRESSION.

PROLONGED SKIN CONTACT CAN CAUSE DERMATITIS LIKE CONDITION

Effects of Overexposure:EYES: TEARING & SLIGHT BURNING SENSATION.

SKIN: DEFATTING & REDNESS. INHALATION: HEADACHE, DIZZINESS, WEAKNESS, LOSS OF COORDINATION.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE

First Aid

First Aid:SKIN: WASH AREA W/MILD SOAP & WATER. IF IRR PERSISTS, GET MED AID. EYES: FLUSH W/WATER FOR AT LEAST 15 MIN. IF IRRI PERSISTS, GET MED AID. INHALATION: REMOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. IF INGESTED: DO NOT INDUCE VOMITING - GET IMMEDIATE MEDICAL ATTENTION

Fire Fighting

Flash Point Method:TCC
Flash Point:158 F 70 C
Lower Limits:ND
Upper Limits:ND
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures:USE PROPER PROTECTIVE EQUIPMENT IN ENCLOSED OR CONFINED AREAS. KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER SPRAY
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DIKE AREA TO CONTAIN. SML: SHOULD BE ABSORBED ON SUITABLE MEDIA & PLACED IN DISPOSAL CONTAINER. LRG: CAN BE VACUUMED & THEN PLACED IN DISPOSAL CONTAINER. DO NOT ALLOW PRODUCT TO ENTER WATERCOURSES.

Handling

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. KEEP AWAY FROM STRONG OXIDIZING MATERIALS. STORE AWAY FROM OPEN FLAMES, SPARKS, ETC. KEEP CONTAINER CLOSED WHEN NOT IN USE
Other Precautions:LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. DO NOT RE-USE CONTAINER

Exposure Controls

Respiratory Protection:IN CONFINED AREAS, USE ORGANIC VAPOR RESPIRATOR
Ventilation:LOCAL EXHAUST
Protective Gloves:RUBBER NEOPRENE
Eye Protection:CHEMICAL SAFETY GOGGLES &/OR FACE SHIELD
Other Protective Equipment:AS NEEDED TO AVOID EYE AND SKIN CONTACT. EYE WASH FOUNTAIN. SAFETY SHOWER.
Work Hygienic Practices:WASH HANDS & FACE AFTER USING & BEFORE EATING, DRINKING OR USING TOILET FACILITIES.
Supplemental Safety and Health
NK

Chemical Properties

HCC:V4
Boiling Pt:B.P. Text:456 F
Melt/Freeze Pt:M.P/F.P Text:ND
Vapor Pres:ND
Vapor Density:ND
Spec Gravity:0.87 @ 77 F
Evaporation Rate & Reference:ND
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER COLORED LIQUID, PETROLEUM-LIKE ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING MATERIALS
Stability Condition to Avoid:OPEN FLAMES, SPARKS, HIGH ENERGY SOURCES
Hazardous Decomposition Products:NONE KNOWN

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.