

KARSEAL PURE CARNAUBA WAX

MSDS Number

BHFBL

National Stock Number

7930-00-985-6750

Product Name

KARSEAL PURE CARNAUBA WAX

Manufacturer

KARSEAL

Product Identification

Product ID:KARSEAL PURE CARNAUBA WAX

MSDS Date:01/01/1987

FSC:7930

NIIN:00-985-6750

MSDS Number: BHFBL

Responsible Party

KARSEAL

11552 HART STREET

NORTH HOLLYWOOD , CA 91605

US

Info Phone: 213-877-0168 OR 818-765-9852

Cage: LO132

Contractor

KARSEAL CORP

NORTH HOLLYWOOD, CA 91605-6228

US

818-765-9852

Cage: 05164

Ingredients

SOLVENT 140

CAS: 64742-47-8

KEROSENE

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CNTRL NERVS SYST DEPRESS. W/HIGH CONCENTRATIONS. AFFECTED PERSONS USUALLY EXPER.COMPLETE RECOVERY WHEN REMOVED FROM EXPOSURE AREA. NOT EXPECTED TO BE ACUTELY TOXIC BY INGST.;INGST. OF THIS PRODUCT O R SUBSEQUENT VOMITING RESULTING IN ASPIRATION OF LIGHT HYDROCRB LIQ. CAN CAUSE PNEUMONITIS IF PROD. LIQUIFIES IN STOMACH

Explanation of Carcinogenicity:SOLVENT 140 & KEROSENE INGREDIENTS CONTAIN TRACE AMTS OF BENZENE WHICH IS A STATE OF CA PROPOSITION 65 SUSPECTED CARCIN

Effects of Overexposure:INGESTION: IRRI, NAUSEA, VOMITING, & DIARRHEA.

SKIN: IRRITATION, DERMATITIS WITH PROLONGED/REPEATED CONTACT. INHALATION: EXCESSIVE OF VAPORS CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, & HEADACHE. EYE: IRRITATION, REDNESS, TEARING, & BLURRED VISION.

Medical Condition Aggravated by Exposure: PRE-EXISTING SKIN, & RESPIRATORY DISORDERS. AS WITH ANY CHEMICAL, THIS PRODUCT MAY AGGRAVATE ALLERGIC CONDITIONS WITH CERTAIN PEOPLE

First Aid

First Aid: INGESTION: SEEK MEDICAL ATTENTION. HAVE PHYSICIAN DETERMINE IF CONDITION OF PATIENT WILL PERMIT VOMIT/EVACUATION OF STOMACH. SKIN: WASH WITH SOAP & WATER. SEEK MEDICAL ATTENTION. IF IRRITATION DEVELOPS. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT SEEK MEDICAL ATTENTION. IF NOT BREATHING GIVE CPR & SEEK MEDICAL ATTENTION. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER. LIFTING LIDS OCCASIONALLY. SEEK MEDICAL ATTENTION.

Fire Fighting

Flash Point Method: TCC

Flash Point: 140°F/60.0°C

Extinguishing Media: CO₂, DRY CHEMICAL, FOAM. USE WATER FOG TO COOL CONTAINERS ONLY

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS IN POSITIVE PRESSURE MODE. COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard: COMBUSTIBLE SOLVENT MIXTURE. EXPOSED CONTAINER MAY SWELL/BURST. AVOID SPREADING BURNING LIQUID WITH WATER. USED FOR COOL PURPOSE. VAPORS > AIR & WILL TRAVEL/IGNITION.

Accidental Release

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. SLIPPERY FLOOR. IF CONTAMINATED PLACE IN A CONTAINER FOR DISPOSAL. IF UNCONTROLLED RELEASE, THE USER SHOULD DETERMINE IF THE RELEASE IS REPORTABLE UNDER APPLICABLE LAWS & REGULATIONS. EYE WASH STATIONS SHOULD BE PRESENT.

Handling

Handling and Storage Precautions: STORE UPRIGHT IN A COOL WELL VENTILATED AREA AWAY FROM OTHER CHEMICAL, FOOD & IGNITION SOURCES. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED (CONTAIN PRODUCT RESIDUES). ALL HAZARD PRECAUTIONS GIVEN IN MSDS MUST BE OBSERVED. MISUSE OF EMPTY CONTAINER MAY BE HAZARDOUS. CUTTING, WELDING, ETC. ON/BY CONTAINER MAY EXPLODE OR CAUSE FIRE.

Exposure Controls

Respiratory Protection: USE APPROVED RESPIRATOR FOR ORGANIC VAPORS. AVOID BREATHING OF VAPORS.

Ventilation: MECHANICAL VENTILATION IS RECOMMENDED

Protective Gloves: SOLVENT RESIST RUBBER (NITRILE, NEOPRENE)

Eye Protection: NOT EXPECTED TO BE A PROBLEM

Other Protective Equipment: EYE WASH FACILITY/SOURCE OF POTABLE WATER. DO NOT WEAR CONTACT LENSES, WILL CONTRIBUTE TO THE SEVERITY OF THE EYE IRRITATION

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING, OR USING TOILET FACILITIES. FOOD SHOULD BE KEPT AWAY FROM THE WORKING AREA.

Supplemental Safety and Health

NOTE TO PHYSICIAN: NOT EXPECTED TO BE ACUTELY TOXIC BY INGESTION. INGESTION OF THIS PRODUCT OR SUBSEQUENT VOMITING RESULTING IN ASPIRATION OF LIGHT HYDROCARBON LIQUID CAN CAUSE PNEUMONITIS IF THE PRODUCT LIQUIDifies IN THE STOMACH. DO NOT GET IN EYESKIN OR CLOTHING. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

Chemical Properties

Boiling Point: B.P. Text: > 300°F

Melt/Freeze Point: M.P./F.P. Text: > 100°F

Vapor Pressure: < 17 MM HG

Vapor Density: > 1 AIR

Evaporation Rate & Reference:< THAN 1 WATER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:SOLID, HYDROCARBON ODOR, YELLOW COLOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, SOME PLASTICS. TEMPERATURE EXTREMESFLAMES, &
IGNITION SOURCES
Hazardous Decomposition Products:CARBON OXIDES

Disposal

Waste Disposal Methods:LIQ. INCINERATION APPROVED SITE. PRODUCT IS AN
OILUNDER THE CLEAN WATER ACT. KEEP OUT OF SURFACE WATER & ANY
WATER COURSES OR SEWER ENTERING OR LEADING TO SUFACE WATERS.
DISPOSE OF ACCORDING TO LOCAL, COUNTY, STATE & FED REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.