
ENAMEL ALKYD GLOSS 15045 STRATA BLUE

MSDS Number

BHFBS

National Stock Number

8010-00-988-1458

Product Name

ENAMEL ALKYD GLOSS 15045 STRATA BLUE

Manufacturer

CON LUX COATINGS INC

Product Identification

Product ID:ENAMEL ALKYD GLOSS 15045 STRATA BLUE

MSDS Date:04/25/1984

FSC:8010

NIIN:00-988-1458

MSDS Number: BHFBS

Responsible Party

CON-LUX COATINGS, INC.

TALMADGE ROAD

EDISON , NJ 08818

US

Emergency Phone: (201) 287-4000

Info Phone: (201) 287-4000

Cage: 60189

Contractor

CON-LUX COATINGS INC

847

EDISON, NJ 08818-0847

US

732-287-4000

Cage: 60189

Ingredients

MINERAL SPIRITS (LEL 1.0)

Fraction By Weight: 51.4%

ACGIH TLV: 500 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Effects of Overexposure:EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE

IRRITATION. INHALATION: MAY IRRITATE

RESPIRATORY TRACT, CAUSE HEADACHE OR DIZZINESS, WHICH IS NORMAL FOR SOLVENT BASE PRODUCTS.

First Aid

First Aid:EYES: FLUSH WITH PLENTY OF WATER.

SKIN: FLUSH WITH PLENTY OF WATER.

INHALATION: REMOVE TO FRESH AIR. IF

IRRITATION PERSISTS, CONSULT A PHYSICIAN.

Fire Fighting

Flash Point Method:TCC
Flash Point:105F/40.56C
Upper Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST
Fire Fighting Procedures:SMOTHER FLAMES W/ONE OF THE FOLLOWING
FOAM,CO2,DRY CHEMICAL,WTR MIST. WATER MAY BE USED TO COOL DOWN
UNOPENED CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE
IN AREAS WHERE SPARKS OR OPEN FLAMES AREPRESENT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
PROLONGED BREATHING OF VAPORS. VENTILATE AREA. CLEAN UP WITH
ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND
PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS.
Other Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE
OF NFPA CLASS II FLAMMABLE LIQUIDS.

Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREAS-USE NIOSH APPROVED FILTER
RESPIRATOR TO REMOVE SOLID AIRBORNEPARTICLES OF OVERSPRAY DURING
SPRAY APPLICATION. RESTRICTED VENTILATN AREAS-USE NIOSH APPROVED
CHEM FILTERS DESIGNED TO REMOVE A COMBINATN OF PARTICULATE/VAPOR.
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION
Protective Gloves:REQUIRED FOR LONG OR REPEATED EXPOSURE.
Eye Protection:SAFETY EYEWEAR
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING.
Supplemental Safety and Health
NK

Chemical Properties

HCC:V3
Boiling Pt:B.P. Text:323F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:51.3

Stability

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL REGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.