https://msdsreport.com/msds/BHFCW

EC-3524 PART A ID 62-3624-0000-0

•

MSDS Number

BHFCW

National Stock Number

8030-01-046-2947

Product Name

EC-3524 PART A ID 62-3624-0000-0

Manufacturer

3M

Product Identification

Product ID:EC-3524 PART A ID 62-3624-0000-0 MSDS Date:05/03/1987 FSC:8030 NIIN:01-046-2947 MSDS Number: BHFCW

Responsible Party

3M

3M CENTER

ST. PAUL , MN 55144-1000

US

Emergency Phone: 612-733-1110

Info Phone: 612-733-1110

Cage: 76381

Contractor

MINNESOTA MINING AND MFG CO, DBA 3M

SAINT PAUL, MN 55144-1000

US

866-556 5712 / 612-733-1110

Cage: 76381

Ingredients

NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:MAY BE IRRITATING TO THE EYES UPON CONTACT SKIN CONTACT:ACUTE EXPOSURE IS MILDLYIRRITATING ,PROLONGED OR REPEATED CONTACT WILL PRODUCE DEFATTING AND RESULT DE RMATITIS. IT MAY CAUSE IRRITATION TO THE RESPITORY AND DIGESTIVE SYSTEMS. Effects of Overexposure:MAY BE IRRITATING TO THE EYES UPON CONTACT. MAY CAUSE AN ALLERGIC SKIN REACTION IN SUSCEPTIBLE INDIVIDUALS. BLURRED VISION IF THE EYE TO LONG.

First Aid

First Aid:EYE CONTACT: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 10 MIN. CALL A DR. SKIN CONTACT:WASH WITH SOAP AND WATER INHALATION:PROVIDE FRESH AIR CALL DR. IF SWALLOWED: DRINK TWO GLASSES OF MILK OR WATER. CALL A DR.

Fire Fighting

Flash Point Method:CC



Flash Point:>200F/93C Lower Limits:NA Upper Limits:NA Extinguishing Media:CO2, FOAM, DRY CHEMICALS Fire Fighting Procedures:FIRE FIGHGTERS SHOULD BE EQUIPPED WITH SCBA WHEN HANDLING THIS MATERIAL Unusual Fire/Explosion Hazard:NONE

•

Accidental Release

Spill Release Procedures:OBSERVE PRECAUTIONS IN ALL SECTIONS.COLLECT SPILLED MATERIAL AND CLEANUP RESIDUE USING ABSORBANT MATERIAL AS NEEDED.PLACE IN A U.S. DEPT. OF TRANSPORTATION APPROVED METAL CONTAINER AND SEAL.

Handling

Handling and Storage Precautions:ND Other Precautions:ND

Exposure Controls

Respiratory Protection:DUST MASK AND MAKE SURE THAT VENTILATION IS GOOD WHEN WORKING WITH CURED MATERIAL FRESH AIR. IF SWALLOWED DRINK LOTS OF MILK AND WATER. Ventilation:MAKE SURE THAT THE CURING STOVE VENTELATED TO THE OUTSIDE AREA. Protective Gloves:IMPERVIOUS GLOVES Eye Protection:SAFETY GLASSES, GOGGLES, Other Protective Equipment:DUST MASK TO HOLD OFF TTHE FUMES, Supplemental Safety and Health KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP OUT OF THE REACH OF CHILDEREN .

Chemical Properties

Boiling Pt:B.P. Text:NA Vapor Pres:NA Vapor Density:NA Spec Gravity:.50 pH:NA Evaporation Rate & Reference:NA Solubility in Water:VERY SLIGHT Appearance and Odor:CHARACTERISTIC AMINE ODOR Percent Volatiles by Volume:0

Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE CARBON MONOXIDE AND CARBONDIOXIDE. Conditions to Avoid Polymerization:IT MAY NOT OCCUR

Disposal

Waste Disposal Methods:2-PART SYSTEM: COMBINE PARTS(A AND B) AND ALLOW TO FULLY CURE.CURED MATERIAL MAY BE PLACED IN A SANITARY LANDFILL IN ACCORDANCE WITH APPLICABLE REGULATIONS AND AUTHORIYIES.INCINERATE "A"IN ACCORDANCE WITH LOCAL REGULATIONS AND AUTHORITIES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.