

COMPLETE FOR FLOORS, 14650-026-030

MSDS Number

BHFDR

National Stock Number

7930-01-105-9136

Product Name

COMPLETE FOR FLOORS, 14650-026-030

Manufacturer

S C JOHNSON AND SON INC

Product Identification

Product ID:COMPLETE FOR FLOORS, 14650-026-030 MSDS Date:06/27/1988 FSC:7930 NIIN:01-105-9136

MSDS Number: BHFDR

Responsible Party

S.C. JOHNSON & SON, INC.

1525 HOWE STREET

RACINE, WI 53403

US

Emergency Phone: 414-631-2777 Preparer: ROBERT B. O'BRIEN

Cage: 3E566

Contractor

SC JOHNSON AND SON INC

RACINE, WI 53403-2236

US

800-725-6737 Cage: 32204

Ingredients

MODIFIED ACRYLIC POLYMER Fraction By Weight: 10-20%

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1-3%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM, VAPOR; 9192

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB



CAS: 111-90-0

RTECS: KK8750000

Fraction By Weight: 1-3%

AMMONIUM HYDROXIDE (SARA III)

CAS: 1336-21-6 RTECS: BQ9625000

Fraction By Weight: 1-3%

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

WATER

CAS: 7732-18-5 RTECS: ZC0110000

._____

Fraction By Weight: 80-90%

OSHA PELNA ACGIH TLV: NA

Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Effects of Overexposure:NA

First Aid

First Aid:NA

Fire Fighting

Flash Point:NA Lower Limits:NA Upper Limits:NA

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures: NORMAL FIRE FIGHTING PROCECURES MAY BE USED.

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures: SWEEP OR SCRAPE UP & CONTAINERIZE. ABSORB W/OIL- DRI OR SIMILAR INERT MATERIAL. DO NOT LET SPILLED OR LEAKING MATERIAL ENTER WATERCOURSE.

Handling

Handling and Storage Precautions: STORE IN COOL, DRY PLACE WITH ADEQUATE VENTILATIONKEEP FROM FREEZING.

Exposure Controls

Respiratory Protection: NO SPECIAL REQUIREMENTS UNDER NORMAL CONDITIONS.

Ventilation:NSR Protective Gloves:NONE

Eye Protection: NONE

Other Protective Equipment: NONE Supplemental Safety and Health

NK

Chemical Properties

Boiling Pt:B.P. Text:>200F Vapor Pres:NA

Vapor Pres:NA Vapor Density:NA Spec Gravity:1.0



pH:9.29.6

Evaporation Rate & Reference:ND Solubility in Water:COMPLETE

Appearance and Odor: OPAQUE, TAN LIQUID W/MILD WAX OR AMMONIACAL ODOR

Percent Volatiles by Volume:NA

Stability

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:WHEN EXPOSED TO FIRE, PRODUCES NORMAL
PRODUCTS OF COMBUSTION

Disposal

Waste Disposal Methods: DISPOSE OF IN COMPLIANCE WITH FEDERAL, STATE, ANDLOCAL REGUIREMENTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.