https://msdsreport.com/msds/BHGTC

# **DURACAL GYPSUM CEMENT**

# **MSDS Number**

BHGTC

# **National Stock Number**

5610-00F009512

## **Product Name**

DURACAL GYPSUM CEMENT

## Manufacturer

UNITED STATES GYPSUM COMPANY

# **Product Identification**

Product ID:DURACAL GYPSUM CEMENT MSDS Date:05/20/1986 FSC:5610 NIIN:00F009512 MSDS Number: BHGTC

# **Responsible Party**

UNITED STATES GYPSUM COMPANY

101 S. WACKER DRIVE

CHICAGO, IL 60606

Emergency Phone: (312) 606-4383

Info Phone: (312) 606-4383

Cage: 61357

## Contractor

UNITED STATES GYPSUM CO

CHICAGO, IL 60606-4302

US

312-606-4000 (EMERG /4542)

Cage: 61357

# Ingredients

PORTLAND CEMENT

CAS: 65997-15-1

RTECS: VV8770000

Fraction By Weight: 1.8-55%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

# Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. SKIN: MAY DEVELOP SUFFICIENT HEAT TO CAUSE BURNS IF A LARGE MASS, SUCH AS A CAST OF A HAND OR ARM, IS KEPT IN CONTACT WHILE HARDENING. INHALATION: DUST IS CONSIDERED A NUIS ANCE DUST. Explanation of Carcinogenicity:NONE Effects of Overexposure:EYES: MAY CAUSE IRRITATION. SKIN: CAUSE BURNS.

# **First Aid**

First Aid: EYES: FLOOD W/WATER FOR 15 MINUTES. SKIN: REMOVE BY WASHING.



IF IRRITATION CONTINUES, SEE PHYSICIAN. INGESTION: GYPSUM CEMENT HARDENS WHEN WETTED AND MAY RESULT IN OBSTRUCTION. SEE PHYSICIAN.

•

# **Fire Fighting**

Flash Point:NONE Extinguishing Media:NOT COMBUSTIBLE Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

#### **Accidental Release**

Spill Release Procedures:SWEEP UP. AVOID CRETING EXCESSIVE DUST. SLURRY MAY PLUG DRAINS.

#### Handling

Handling and Storage Precautions: DEW POINT CONDITIONS OR OTHER CONDITIONS CAUSING PRESENCE OF LIQUID WATER DURING STORAGE WILL HARDEN GYPSUM CEMENT.

## **Exposure Controls**

Respiratory Protection:NIOSH APPROVED NUISANCE DUST RESPIRATOR IF >TLV. Ventilation:PROVIDE MECHANICAL & LOCAL EXHAUST VENTILATION TO KEEP >TLV Protective Gloves:IF DUST OR SLURRY IS IRRITATING Eye Protection:DUST GOGGLES, SAFETY GLASSES Supplemental Safety and Health

## **Chemical Properties**

Melt/Freeze Pt:M.P/F.P Text:1450C Spec Gravity:2.7 Solubility in Water:0.2% Appearance and Odor:WHITE, OFF-WHITE, GRAY OR PIGMENTED POWDER. LOW ODOR.

# Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:SO2 & CAO

#### Disposal

Waste Disposal Methods: IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.