

Y 1608 WOODMASTER STAIN

MSDS Number

BHLJL

National Stock Number

8010-00F009659

Product Name

Y 1608 WOODMASTER STAIN

Manufacturer

GLIDDEN COATINGS AND RESINS DIV

Product Identification

Product ID:Y 1608 WOODMASTER STAIN

MSDS Date:06/01/1987

FSC:8010

NIIN:00F009659

MSDS Number: BHLJL

Responsible Party

GLIDDEN COATINGS & RESINS DIVISION

925 EUCLID AVENUE

CLEVELAND , OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: DO304

Contractor

GLIDDEN COATINGS & RESINS DIVISION

15049

CLEVELAND, OH 44115

US

(216) 826-5566

Cage: DO304

Ingredients

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 69%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 1 - 3%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: FATIGUE, DIZZINESS, HEADACHE, CNS DEPRESSION. IRRITATION OF EYES, SKIN, RESP TRACT. SKIN: DERMATITIS, DEFATTING. EYE: BLURRED VISION, TEARING/REDNESS. INGESTION: NAUSEA, VOMITING, DIARRHEA , DIGESTIVE SYSTEM PROBLEMS, ANESTHETICEFFECT, NARCOSIS, SEVERE LUNG IRRITATION/DAMAGE, & UNCONSCIOUSNESS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE DERMATITIS. EYE: BLURRED VISION, TEARING/REDNESS. OVEREXPOS URE TO SOLVENTS CAUSES PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Medical Cond Aggravated by Exposure:DERMATITIS

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE/SUPPORT BREATHING. SKIN: WASH OFF QUICKLY W/PLENTY OF SOAP & WATER. REMOVE/WASH CONTAMINATED CLOTHING BEFORE RE-USE. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR A T LEAST 15 MINS. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: OBTAIN MEDICAL TREATMENT IMMEDIATELY.

Fire Fighting

Flash Point Method:SCC
Flash Point:102F
Lower Limits:0.7%
Extinguishing Media:DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER MAY BE USED TO COOL & PROTECT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT/FLAME. VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.

Accidental Release

Spill Release Procedures:COMPLY W/ALL APPLICABLE HEALTH & ENVIRONMENTAL REGS. VENTILATE AREA. SPILLS MAY BE COLLECTED W/ABSORBENT MATERIALS. LARGE SPILLS: SHUT OFF LEAK IF SAFE TO DO SO. DIKE/CONTAIN SPILL. PUMP TO STORAGE/SA LVAGE VESSELS. USE ABSORBENT TO PICK UPRESIDUE.

Handling

Handling and Storage Precautions:STORE SPARKS, & OPEN FLAME. USE ONLY W/ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:AVOID CONTACT W/SKIN, EYES, & BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

Exposure Controls

Respiratory Protection:IF >TLV IS REQUIRED, US NIOSH/MSHA APPROVED RESPIRATORS. IF SANDING IS DONE, WEAR A DUSTMASK TO AVOID BREATHING OF SANDING DUST.
Ventilation:PROVIDE LOCAL EXHAUST/MECHANICAL VENTILATION TO KEEP Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES, GOGGLES
Other Protective Equipment:SAFETY SHOWER, EYE WASH.
Work Hygienic Practices:REMOVE/WASH CONTAMINATED CLOTHING BEFORE RE-USE.
Supplemental Safety and Health
WT PER GAL: 7.34 LBS.

Chemical Properties

Boiling Pt:B.P. Text:308-374F
Percent Volatiles by Volume:77.87%

Stability

Stability Indicator/Materials to Avoid: YES

OXIDIZERS, ACIDS, BASES, AMINES

Stability Condition to Avoid: ELEVATED TEMPERATURES, HEAT, SPARKS, & OPEN FLAME.

Hazardous Decomposition Products: CO, CO₂

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.