https://msdsreport.com/msds/BHNBW

# **FISH EYE ELIMINATOR**

**MSDS Number** 

BHNBW

**National Stock Number** 

8010-01-046-5006

**Product Name** 

FISH EYE ELIMINATOR

Manufacturer

E I DU PONT DE NEMOURS AND CO (INC )

### **Product Identification**

Product ID:FISH EYE ELIMINATOR MSDS Date:12/17/1988 FSC:8010 NIIN:01-046-5006 MSDS Number: BHNBW

### **Responsible Party**

E.I. DU PONT DE NEMOURS & CO. (INC.)

AUTOMOTIVE PRODUCTS DEPARTMENT

WILMINGTON, DE 19898

US

Emergency Phone: 800-441-3637 OR 800-424-9300

Info Phone: 800-441-7515

Cage: 18773

### Contractor

E.I. DU PONT DE NEMOURS & CO., INC. WILMINGTON, DE 19898 US

800-441-7515

Cage: 18773

## Ingredients

SILICONE RESIN CAS: 9016-00-6 RTECS: TQ2690000

N-BUTYL ACETATE (SARA III) CAS: 123-86-4 RTECS: AF7350000 OSHA PEL150 PPM/200 STEL ACGIH TLV: 150 PPM/200STEL;9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS



CAS: 110-19-0

RTECS: AI4025000

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

#### Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. BUTYL ACETATE MAY RESULT IN LIVER/KIDNEY INJURY

•

Effects of Overexposure:EYE:MAY CAUSE IRRITATION OR BURNING OF THE EYES; SKIN:REPEATED/PROLONGED LIQUID CONTACT MAY CAUSE SKIN IRRITATION W/DISCOMFORT & DERMATITIS. INHAL:MAY CAUSE NOSE/THROAT IRRITATION,H EADACHES,DIZZINESS,NAUSEA,STAGGERINGGAIT,CONFUSION, OR UNCONSCIOUSNESS; INGST:GASTROINTESTINAL DISTRESS. Medical Cond Aggravated by Exposure:BUTYL ACETATE MAY RESULT IN LIVER/KIDNEY INJURY

#### **First Aid**

First Aid:EYE:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES CALL A PHYSICIAN. SKIN:WASH WITH SOAP AND WATER IF IRRITATION OCCURS CONTACT A PHYSICIAN. INHAL:REMOVE TO FRESH AIR IF NOT BREATHI NG GIVE CPR.IF BREATHING DIFFICULTYPERSISTS OR OCCURS LATER CONSULT A PHYSICIAN. INGST:CALL A PHYSICIAN IMMEDIATELY & HAVE NAMES OF INGREDIENTS AVAILABLE.

### **Fire Fighting**

Flash Point Method:CC Flash Point:20F/-7C Lower Limits:1.2 Upper Limits:7.6 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT,INCLUDING SCBA, IS RECOMMENDED. WATER FROM FOG NOZZLESMAY BE USED TO PREVENT PRESSURE BUILD UP. Unusual Fire/Explosion Hazard:WHEN HEATED ABOVE THE FLASHPOINT,EMITS FLAMMABLE VAPORS WHICH.WHEN MIXED W/AIR CAN BURN OR BE

FLAMMABLE VAPORS WHICH, WHEN MIXED W/AIR CAN BURN OR BE EXPLOSIVE.FINE MIST/SPRAYS MAYBE FLAMMABLE AT TEMP BELOW FLASHPT.

#### **Accidental Release**

Spill Release Procedures: REMOVE SOURCES OF IGNITION. PREVENT SKIN CONTACT AND BREATHING OF VAPOR. CONFINE AND REMOVE WITH INERT ABSORBENT. VENTILATE AREA. DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS.

#### Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,& FLAME.CLOSE CONTAINERAFTER EACH USE.GROUND CONTNRS WHEN POURING.DO NOT STORE ABOVE 120F. Other Precautions:DO NOT SAND,FLAME CUT,BRAZE OR WELD DRY COATING WITHOUT A NIOSH/MSHA APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. OBSERVE LABEL PRECAUTIONS.

#### **Exposure Controls**

Respiratory Protection: WEAR PROPERLY FITTED VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR USE W/PAINTS DURING APPLICATION & UNTIL ALL VAPORS/SPRAY MISTS ARE EXHAUSTED. Ventilation: PROVIDE SUFFICIENT VENTILATION IN VOLUME & PATTERN TO KEEP CONTAMINANTS BELOW APPL OSHA REQUIRE & OTHER EXPOSURE LIMITS



https://msdsreport.com/msds/BHNBW

Protective Gloves:NEOPRENE GLOVES Eye Protection:CHEM GOGGLES ARE PREFERD TO PREVNT IRRIT Other Protective Equipment:COVERALLS ARE RECOMMENDED. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING. Supplemental Safety and Health PROTECTIVE CREAMS MAY BE USED FOR EASE OF CLEAN UP. DO NOT USE FOR PROTECTION. IF SAFETY GLASSES ARE SUBSTITUTED INCLUDE SPLASH GUARD OR SIDE SHIELDS.

•

### **Chemical Properties**

HCC:F3 Boiling Pt:B.P. Text:112-149C Vapor Density:>AIR Evaporation Rate & Reference:SLOWER THAN ETHER Solubility in Water:SLIGHT Percent Volatiles by Volume:53.1

### Stability

Stability Indicator/Materials to Avoid:YES NONE Hazardous Decomposition Products:CO,CO2,SMOKE,OXIDES OF HEAVY METALS

#### Disposal

Waste Disposal Methods:DO NOT INCINERATE IN CLOSED CONTAINERS. INCINERATEABSORBED MATERIAL IN ACCORDANCE WITH FEDERAL,STATEAND LOCAL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.