

WHITE MINERAL OIL 190 USP

MSDS Number

BHSKW

National Stock Number

9150-00F010417

Product Name

WHITE MINERAL OIL 190 USP

Manufacturer

G C LUBRICANTS COMPANY

Product Identification

Product ID:WHITE MINERAL OIL 190 USP

MSDS Date:11/01/1985

FSC:9150

NIIN:00F010417

MSDS Number: BHSKW

Responsible Party

G-C LUBRICANTS COMPANY

977 BRANSTEN ROAD

SAN CARLOS , CA 94070

Emergency Phone: (800) 424-9300

Info Phone: (415) 592-1050

Cage: 0HJB5

Contractor

G-C LUBRICANTS COMPANY

SAN CARLOS, CA 94070

(415) 592-1050

Cage: 0HJB5

Ingredients

MINERAL OIL (WHITE)

CAS: 8040-47-5

Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

First Aid

First Aid:INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DON'T INDUCE VOMITING, CONSULT PHYSICIAN. INHALATION: MOVE THE VICTIM AWAY FROM THE AREA TO FRESH AIR. RESUSCITATE AND ADMINISTER OXYG EN. CONSULT PHYSICIAN. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEE DOCTOR. SKIN: WASH AREAS W/PLENTY OF WATER. WASH ALL CONTAMINATED CLOTHING BEFORE RE-USE.

Fire Fighting

Flash Point:410F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS WHEN THIS MATERIAL IS INVOLVED IN A FIRE.

Unusual Fire/Explosion Hazard:TREAT AS AN OIL WHEN EXPOSED TO FIRE.

OVERPRESSURIZATION WILL OCCUR IF THE CONTAINER IS EXPOSED TO FIRE.

USE WATER TO COOL FIRE-EXPOSED CONTAINERS.

Accidental Release

Spill Release Procedures:CONTAIN W/ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:USE NORMAL GOOD PRACTICES.

Other Precautions:WASH ALL CONTAMINATED CLOTHING BEFORE RE-USE. ALWAYS WASH HANDS PRIOR TO SMOKING OR EATING.

Exposure Controls

Ventilation:LOCAL EXHAUST: SUGGESTED. MECHANICAL: ACCEPTABLE

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE RE-USE.

ALWAYS WASH HANDS PRIOR TO SMOKING OR EATING.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:571F

Vapor Pres:1

Vapor Density:1

Spec Gravity:0.87

Evaporation Rate & Reference:(BU AC = 1): 1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TRANSPARENT LIQUID

Percent Volatiles by Volume:0.0%

Stability

Stability Indicator/Materials to Avoid:NO

STRONG OXIDIZING AGENTS, NITRIC ACID, HYDROGEN PEROXIDE & CHROMIC ACID.

Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:INCINERATE OR BURY IN A LICENSED CHEMICAL WASTE DISPOSAL SITE IN ACCORDANCE W/LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.