

TT-P-24E TYIII GRAY 24692

MSDS Number

BHWZM

National Stock Number

8010-00-582-4672

Product Name

TT-P-24E TYIII GRAY 24692

Manufacturer

TRIAD PAINT AND CHEMICAL CORP

Product Identification

Product ID:TT-P-24E TYIII GRAY 24692

MSDS Date:01/01/1987

FSC:8010

NIIN:00-582-4672

MSDS Number: BHWZM

Responsible Party

TRIAD PAINT AND CHEMICAL CORP

810 EVERGREEN AVENUE

BROOKLYN , NY 11207

US

Emergency Phone: (718) 443-2778

Info Phone: (718) 443-2778

Cage: 33151

Contractor

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

201-437-6501

Cage: 33151

Ingredients

MINERAIL SPIRITS

CAS: 64741-41-9

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:VAPOR MIGHT BE IRRITATING TO EYES,
NOSE AND THROAT. EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE,
DIZZINESS AND NAUSEA. DEFATTING TO SKIN.

Effects of Overexposure:MAY RESULT IN HEADACHES DIZZINESS AND NAUESA

First Aid

First Aid:INHALATION: PROVIDE FRESH AIR AND REST. SKIN: WASH AFFECTED
AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. DRINK
ONE OR TWO GLASSES OF WATER TO DILUTE. EYE: FLUSH WITH WATER FOR
15 MIN UTES.

Fire Fighting

Flash Point Method:PMCC

Flash Point:41C/105F

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:FOAM, CO2, DRY CHEMICALS

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED RESPIRATORS. WATER STREAM WILL SPREAD OIL FIRES. DO NOT USE WATER.

Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION. VAPOR FORMS EXPLOSIVE MIXTURE BETWEEN UPPER AND LOWER EXPLOSIVE UNITS.

Accidental Release

Spill Release Procedures:AVOID FLAME AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. WIPE UP SPILL WITH INERT ABSORBENTS AND NON SPARKING TOOLS. SAFELY DISCARD SATURATED ABSORBENTS. AVOID PROLONGED BREATHING OF VAPORS

Handling

Handling and Storage Precautions:AVOID OPEN FLAMES AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR.

Exposure Controls

Respiratory Protection:ORGANIC CANISTER MASK AS ALL PACK VENTILATION IS INADEQUATE

Ventilation:LOCAL EXHAUST IS RECOMMENDED.

Protective Gloves:NEOPRENE RUBBER GLOVES

Eye Protection:CHEMICAL SAFETY GLASSES

Supplemental Safety and Health

NK

Chemical Properties

Boiling Pt:B.P. Text:315-352F

Vapor Pres:100F

Vapor Density:5.0

Spec Gravity:1.645

Evaporation Rate & Reference:.13

Solubility in Water:NEG

Appearance and Odor:GRAY COLORED LIQUID. HYDROCARBON ODOR

Percent Volatiles by Volume:37.3

Stability

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:WARM STORAGE AND IGNITION SOURCES

Hazardous Decomposition Products:CO, CO2, ACID FUMES, AND SMOKE WHEN COMBUSTED.

Disposal

Waste Disposal Methods:DISPOSAL PROCEDURES MUST COMPLY WITH LOCAL, STATE,AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.