

# **NEYORO CB**

# **MSDS Number**

BJBMX

### **National Stock Number**

6520-00F012054

#### **Product Name**

**NEYORO CB** 

#### Manufacturer

J M NEY COMPANY

### **Product Identification**

Product ID: NEYORO CB MSDS Date: 01/01/1987 FSC:6520 NIIN:00F012054 MSDS Number: BJBMX

# **Responsible Party**

J.M. NEY COMPANY

**NEY INDUSTRIAL PARK** 

BLOOMFIELD, CT 06002

Emergency Phone: (203) 242-2281

Info Phone: (203) 242-2281

Cage: FO552 **Contractor** 

**NEY DENTAL INCORPORATED** 

BLOOMFIELD, CT 06002-5000

US

800-243-1942/203-242-2281

Cage: 43710 **Ingredients** 

SILVER (SARA III) CAS: 7440-22-4

RTECS: VW3500000

Fraction By Weight: 22.5% OSHA PEL0.01 MG/M3

ACGIH TLV: 0.1 MG/M3; 9192 EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

COPPER (SARA III)

CAS: 7440-50-8 RTECS: GL5325000

Fraction By Weight: 13.5%

OSHA PEL0.1MG/M3 FUME/1 DUST



ACGIH TLV: 0.2MG/M3 FUME; 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

ZINC (SARA III)

CAS: 7440-66-6

RTECS: ZG8600000

Fraction By Weight: 1%

OSHA PEL10 MG ZNO/M3

ACGIH TLV: 10 MG ZNO/M3; 9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

#### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: SKIN: GRAY PIGMENTATION, IRRITATION,

CUTS, & BURNS. INGESTION: GASTROINTESTINAL TRACT EFFECTS.

INHALATION: PULMONARY SYSTEM EFFECTS & OXIDES OF ZINC ARE TOXIC.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: SKIN: GRAY PIGMENTATION, IRRITATION, CUTS, & BURNS. INGESTION: GASTROINTESTINAL TRACT EFFECTS. INHALATION:

PULMONARY SYSTEM EFFECTS & OXIDES OF ZINC ARE TOXIC.

### First Aid

First Aid: INHALATION: REMOVE FROM EXPOSURE & OBTAIN PROMPT MEDICAL ATTENTION.

## **Fire Fighting**

Unusual Fire/Explosion Hazard: ZINC DUST & SILVER DUST IS A MODERATE EXPLOSION HAZARD.

#### **Accidental Release**

Spill Release Procedures:IF LARGE QUANTITIES OF DUST ARE GENERATED, USE INDUSTRIAL VACUUM TO CLEAN UP. MOLTEN METAL SHOULD BE ALLOWED TO SOLIDIFY BEFORE CLEAN UP.

#### Handling

Handling and Storage Precautions:PROVIDE PROTECTIVE EQUIPMENT WHEN CUTTING, GRINDING, SOLDERING, WELDING, MELTING, MACHINING, & HANDLING OF NON-FERROUS METALS.

## **Exposure Controls**

Respiratory Protection: WEAR WHEN CUTTING, GRINDING, SOLDERING OR WELDING.

Ventilation:LOCAL EXHAUST TO KEEP DUST, MIST OR FUMES Protective Gloves:RECOMMENDED WHEN GRINDING OR MELTING

Eye Protection: RECOMMENDED Supplemental Safety and Health

ALLOY PRODUCTS ARE SOLID METALS SHAPED AS WIRE, PLATE, STRIP OR IN FINISHED FORMS AS INGOTS, NUGGETS, ELECTRICAL CONTACT ASSEMBLIES,

SWITCHES, OR AS OTHER FORMS FOR ELECTRONIC & DENTAL USE.

## **Chemical Properties**

Solubility in Water: NONE

Appearance and Odor: SOLID METALS-WIRE, PLATE, STRIP, INGOTS, NUGGETS.

#### Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:WELDING FUMES



# **Disposal**

Waste Disposal Methods: DISPOSAL OF DUST USING APPROVED METHODS CONSISTANT W/APPLICABLE LOCAL, STATE, & FEDERAL REGULATIONS. MOLTEN METAL SHOULD BE RECLAIMED USING STANDARD INDUSTRIAL PRACTICES SUCH AS REMELTING & REFINING.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.