

## **ALCOHOL-DENATURED**

### **MSDS Number**

BJBWG

### **National Stock Number**

6810-00F012186

### **Product Name**

ALCOHOL-DENATURED

### **Manufacturer**

HENRY SCHEIN INC

### **Product Identification**

Product ID:ALCOHOL-DENATURED

MSDS Date:01/01/1987

FSC:6810

NIIN:00F012186

MSDS Number: BJBWG

### **Responsible Party**

HENRY SCHEIN INC

5 HARBOR PARK DR

PORT WASHINGTON , NY 11050

Emergency Phone: (516) 621-4300

Info Phone: (516) 621-4300

Cage: 64682

### **Contractor**

HENRY SCHEIN INC

PORT WASHINGTON, NY 11050

(516) 621-4300

Cage: 64682

### **Ingredients**

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

### **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: MAY CAUSE SYSTEMIC POISONING.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: MAY CAUSE SYSTEMIC POISONING.

### **First Aid**

First Aid:EYES: FLUSH W/PLENTY OF WATER. CONTACT PHYSICIAN. SKIN: WASH CONTAMINATED AREA W/SOAP & WATER. INGESTION: INDUCE VOMITING. GIVE 2 GLASSES WATER & STICK FINGER DOWN THROAT OR DILUTE POINT W/WATER.

INHALATION: REMOVE FROM CONTAMINATED AREA IMMEDIATELY.

## Fire Fighting

Flash Point Method: TOC

Flash Point: 60F

Lower Limits: 5.5%

Upper Limits: 36.5

Extinguishing Media: ALCOHOL OR POLYMER FOAM, CO2 OR DRY CHEMICAL

Fire Fighting Procedures: ADDITION OF WATER TO BURNING FUEL WILL REDUCE THE INTENSITY OF FLAME.

Unusual Fire/Explosion Hazard: NONE

## Accidental Release

Spill Release Procedures: ELIMINATE IGNITION SOURCE. CONTAIN SPILL FOR SALVAGE OR DISPOSAL. USE OF ANY DILUTION WATER SHOULD BE CLOSELY CONTROLLED TO MINIMIZE SPILL VOLUME. AVOID RUN-OFF INTO STORM SEWERS & DITCHES WHICH LEAD TO NATURAL WATERWAYS. ADVISE AUTHORITIES OF SPILL.

## Handling

Handling and Storage Precautions: DON'T LEAVE CONTAINER OPEN. USE W/ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED CONTACT W/SKIN.

## Exposure Controls

Respiratory Protection: SELF-CONTAINED BREATHING APPARATUS.

Ventilation: MECHANICAL: ACCEPTABLE. LOCAL EXHAUST: PREFERABLE

Protective Gloves: NEOPRENE, RUBBER

Eye Protection: CHEMICAL SAFETY GOGGLES

Other Protective Equipment: IMPERVIOUS APRON, BOOTS, EYE BATH & SAFETY SHOWER.

Supplemental Safety and Health

## Chemical Properties

Boiling Pt: B.P. Text: 64.6F

Vapor Pres: 96.0

Vapor Density: 1.11

Spec Gravity: 0.7925

Evaporation Rate & Reference: (BU AC = 1): 1

Solubility in Water: COMPLETE

Appearance and Odor: WATER-WHITE LIQUID; CHARACTERISTIC ODOR.

Percent Volatiles by Volume: 100%

## Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: HEAT, SPARKS & FIRE

## Disposal

Waste Disposal Methods: CHEMICAL INCINERATOR; BIOLOGICAL TREATMENT; LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.