

ACOUSTONE-FIRE RATED & REGULATOR MINERAL FIBER

MSDS Number

BJCBX

National Stock Number

5640-00F012272

Product Name

ACOUSTONE-FIRE RATED & REGULATOR MINERAL FIBER

Manufacturer

USG INTERIORS INC

Product Identification

Product ID:ACOUSTONE-FIRE RATED & REGULATOR MINERAL FIBER

MSDS Date:02/01/1991

FSC:5640 NIIN:00F012272 MSDS Number: BJCBX

Responsible Party

.....

USG INTERIORS INC

101 S WACKER DR

CHICAGO, IL 60606-4385

US

Emergency Phone: 312-606-3759/312-606-4382

Info Phone: 312-606-5868

Cage: 0PB81

Contractor

USG INTERIORS INC

CHICAGO, IL 60606

US

312-321-4000 Cage: 0PB81

Ingredients

MINERAL FIBER

OSHA PEL15 MG/CUM (TOTAL) ACGIH TLV: 10 MG/CUM (TOTAL)

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7 RTECS: VV7330000

Fraction By Weight: TRACE OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO



Health Hazards Acute and Chronic: WHEN THESE PANELS OR TILES ARE CUT OR TRIMMED, ESPECIALLY W/POWER TOOLS, THE RESULTING DUST MAY CAUSE TRANSITORY MECHANICAL IRRITATION TO SKIN/EYES/RESPIRATORY TRACT. MAY CAUSE LUNG CANCER, ESPECIALLY IF BREATHED IN CONJUNCTION W/SMOKING; SILICOSIS, OTHER LUNG DISEASE.

Explanation of Carcinogenicity: SEE INGREDIENTS.

Effects of Overexposure: SKIN/EYES: IRRITATION. INHALATION: RESPIRATORY TRACT IRRITATION (NOSE & THROAT).

First Aid

First Aid: EYES: FLUSH W/WATER. IF IRRITATION CONTINUES, CALL PHYSICIAN. SKIN: WASH PARTICLES FROM SKIN W/SOAP & WATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point: NON-COMBUSTIBLE

Accidental Release

Spill Release Procedures: NORMAL CLEAN UP PROCEDURES.

Handling

Handling and Storage Precautions: DON'T SMOKE WHILE USING. CUT/TRIM W/KNIFE/RAZOR/HAND SAW. DON'T CUT W/POWER EQUIPMENT. AVOID CONTACT W/SKIN & EYES.

Other Precautions: WHEN THESE TILES/PANELS ARE CUT, ESPECIALLY W/POWER TOOLS, THE RESULTING DUST CONTAINS MAN-MADE VITREOUS FIBER & MAY CONTAIN RESPIRABLE CRYSTALLINE SILICA.

Exposure Controls

Respiratory Protection: NIOSH APPROVED DUST RESPIRATOR IF THE TLV/PEL IS EXCEEDED. IF USING POWER EQUIPMENT USE DUST COLLECTOR & A NIOSH APPROVED DUST MASK.

Ventilation: IF CUTTING/TRIMMING W/POWER EQUIPMENT: DUST COLLECTORS/LOCAL EXHAUST VENTILATION MUST BE USED.

Protective Gloves: RECOMMENDED

Eye Protection: TIGHT FITTING GOGGLES/SAFETY GLASSES

Other Protective Equipment: LONG SLEEVED/LOOSE FITTING CLOTHING CLOSED AT NECK/WRISTS.

Work Hygienic Practices: WASH WORK CLOTHING SEPARATELY FROM OTHER CLOTHING. RINSE WASHER THOROUGHLY AFTER USE.

Supplemental Safety and Health

THIS MATERIAL IS MOLDED OR WATER FELTED TILES OR PANELS MADE OF SLAG WOOL OR TILES OR PANELS OF SPUN GLASS WOOL. BACK MAY BE UNPAINTED, PAINTED, OR COVERED W/ALUMINUM FOIL. SOME PRODUCTS ARE WRAPPED O R FACED W/FABRIC OR VINYL FILM.

Chemical Properties

Appearance and Odor: WHITE TO GRAY, OR YELLOW CORE W/PAINTED FACE. SEE SUPP.

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods: SANITARY LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.