

UNITEK SEALANT LACQUER 15672

MSDS Number

BJCWC

National Stock Number

6520-01-266-9063

Product Name

UNITEK SEALANT LACQUER 15672

Manufacturer

UNITEK CORP

Product Identification

Product ID:UNITEK SEALANT LACQUER 15672

MSDS Date:01/01/1985

FSC:6520

NIIN:01-266-9063

MSDS Number: BJCWC

Responsible Party

UNITEK CORPORATION

2724 SOUTH PECK ROAD

MONROVIA , CA 91016

Emergency Phone: (818) 445-7960

Info Phone: (818) 445-7960

Preparer: J.E. PENICK

Cage: 90444

Contractor

UNITEK CORPORATION

MONROVIA, CA 91016-5005

(213) 445-7960

Cage: 90444

Ingredients

TERT-BUTYL ACETATE (SARA III)

CAS: 540-88-5

RTECS: AF7400000

Fraction By Weight: 80%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 15%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF THE NOSE,
THROAT & EYES, WEAKNESS, DROWSINESS, & UNCONSCIOUSNESS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: MAY CAUSE WEAKNESS, DROWSINESS,
UNCONSCIOUSNESS & IRRITATION OF THE THROAT, NOSE & EYES.

First Aid

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER. INHALATION: MOVE
INDIVIDUAL TO FRESH AIR. IF BREATHING STOPPED, PERFORM ARTIFICIAL
RESPIRATION. INGESTION: INDUCE VOMITING. SEEK MED ATTN.

Fire Fighting

Flash Point Method:CC
Flash Point:76F
Lower Limits:1.7%
Upper Limits:7.6%
Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL

Accidental Release

Spill Release Procedures:VENTILATE AREA OF SPILL. REMOVE ALL IGNITION
SOURCES. ABSORB IN SUITABLE MATERIAL, SUCH AS VERMICULITE, SAND &
DISPOSE.

Handling

Handling and Storage Precautions:PRACTICE REASONABLE CARE & CAUTION.
Other Precautions:T-BUTYL ACETATE MAY SOFTEN OR DISSOLVE PLASTICS.

Exposure Controls

Respiratory Protection:MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS.
Ventilation:LOCAL EXHAUST: GENERAL DILUTION VENTILATION
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES, FULL FACE SHIELD
Other Protective Equipment:IMPERVIOUS CLOTHING
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:275F
Vapor Pres:15
Vapor Density:4.0
Spec Gravity:0.87
Evaporation Rate & Reference:(BU AC = 1): 1
Solubility in Water:SLIGHT
Appearance and Odor:SLIGHTLY HAZY, COLORLESS LIQUID W/A FRUITY ODOR

Stability

Stability Indicator/Materials to Avoid:YES
NITRATES, STRONG OXIDIZERS, ACIDS, ALKALIES & PLASTICS
Stability Condition to Avoid:HEAT & IGNITION SOURCES
Hazardous Decomposition Products:TOXIC GASES & VAPORS

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL ENVIRONMENTAL PROTECTION REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.