

# **KAVO QUICK SPRAY**

## **MSDS Number**

**BJCXP** 

## **National Stock Number**

6520-01-308-1034

## **Product Name**

KAVO QUICK SPRAY

#### Manufacturer

KAVO AMERICA CORP

## **Product Identification**

Product ID:KAVO QUICK SPRAY MSDS Date:05/15/1986 FSC:6520 NIIN:01-308-1034

MSDS Number: BJCXP

# **Responsible Party**

KAVO AMERICA CORP

2401 W. HASSELL RD SUITE 1550

HOFFMAN ESTATES, IL 30411

Emergency Phone: (312) 885-3855

Info Phone: (312) 885-3855

Cage: 14487

Contractor

KAVO AMERICA CORP

HOFFMAN ESTATES, IL 30411

(312) 885-3855 Cage: 14487

## **Ingredients**

TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)

CAS: 75-69-4 RTECS: PB6125000 OSHA PEL1000 PPM

ACGIH TLV: C, 1000 PPM; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000 OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIANT; 9192



CAS: 106-97-8 RTECS: EJ4200000 OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192

#### Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:YES

Health Hazards Acute and Chronic:SKIN: FROSTBITE & ITCHING. INHALATION:

DIZZINESS, DISORIENTATION, EXCITATION & AFFECTS RESPIRATION.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: SKIN: FROSTBITE & ITCHING. INHALATION: DIZZINESS, DISORIENTATION, EXCITATION, & AFFECTS RESPIRATIN.

#### First Aid

First Aid: INHALATION: AFFECTED AREA, SEEK PROFESSIONAL HELP.

# Fire Fighting

Flash Point:-80C Lower Limits:1.5% Upper Limits:8.4%

Extinguishing Media: CO2, FOAM EXTINGUISHER, POWDER EXTINGUISHER

CLASSIFICATION A - 0.

## **Accidental Release**

Spill Release Procedures: GENERALLY VENTILATE AREA, USE STANDARD OIL DRYING COMPOUND.

## Handling

Handling and Storage Precautions:PROTECT FROM SUNLIGHT & DON'T EXPOSE TO TEMPERATURES EXCEEDING 50C. DO NOT PIERCE OR BURN OR SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL. Other Precautions:DO NOT INCINERATE CAN.

## **Exposure Controls**

Respiratory Protection: NOT NEEDED UNDER NORMAL USE.

Ventilation: MECHANICAL: LOCAL CODE ACCEPTED BUILDING VENTILATION.

Protective Gloves: NONE NEEDED UNDER NORMAL USE

Eye Protection:NOT NEEDED Other Protective Equipment:NONE Supplemental Safety and Health

## **Chemical Properties**

Boiling Pt:B.P. Text:-0.5C Vapor Pres:900 Vapor Density:0.548 Spec Gravity:1.045

Evaporation Rate & Reference: (BU AC = 1): 168 Appearance and Odor: CLEAR; ODORLESS LIQUID

# **Stability**

Stability Indicator/Materials to Avoid:NO INCANDESCENT MATERIAL Stability Condition to Avoid:SUNLIGHT, DON'T EXPOSE TO TEMPERATURES EXCEEDING 50C. DON'T PIERCE OR BURN. DON'T SPRAY ON A NAKED FLAME. Hazardous Decomposition Products:NONE

#### Disposal

Waste Disposal Methods: SAME AS FOR WASTE OIL, DO NOT MIX WITH ACIDS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and



disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.