

## **A24 A 11 MEDIUM GRAY ACRYLIC LATEX FLOOR EN**

### **MSDS Number**

BJCZN

### **National Stock Number**

8010-00F012458

### **Product Name**

A24 A 11 MEDIUM GRAY ACRYLIC LATEX FLOOR EN

### **Manufacturer**

SHERWIN WILLIAMS COMPANY

### **Product Identification**

Product ID:A24 A 11 MEDIUM GRAY ACRYLIC LATEX FLOOR EN

MSDS Date:04/04/1988

FSC:8010

NIIN:00F012458

MSDS Number: BJCZN

### **Responsible Party**

SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVENUE N.W.

CLEVELAND , OH 44115

Emergency Phone: (216) 566-2917

Info Phone: (216) 566-2902

Cage: 54636

### **Contractor**

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

### **Ingredients**

2-(2-BUTOXYETHYOXY)-ETHANOL, DIETHYLENE GLYCOL MONOBUTYL

CAS: 112-34-5

RTECS: KJ9100000

Fraction By Weight:

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 0-5%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 0-20%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

3)

CAS: 1308-38-9

RTECS: GB6475000

Fraction By Weight:

OSHA PEL1 MG/CUM

ACGIH TLV: 0.5 MG/CUM

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF THE UPPER RESPIRATORY SYSTEM, HEADACHE, NAUSEA, & DIZZINESS. SKIN: IRRITATION, REDNESS, ITCHING, & BURNING SENSATION. EYES: IRRITATION.

Explanation of Carcinogenicity:CRYSTALLINE SILICA MAY POSSIBLY CAUSE CANCER.

Effects of Overexposure:INHALATION: IRRITATION OF THE UPPER RESPIRATORY SYSTEM, HEADACHE, NAUSEA, DIZZINESS, CRYSTALLINE SILICA MAY CAUSE LUNG DAMAGE (SILICOSIS) & POSSIBLY CANCER, & ADVERSE EFFECTS TO THE REPRODUCTIVE SYSTE . SKIN: IRRITATION, REDNESS, ITCHING, & BURNING SENSATION. EYES: IRRITATION.

## First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE RE-USE. EYES: FLUSH W/WATER FO R 15 MINUTES. GET MEDICAL ATTENTION.

## Fire Fighting

Flash Point Method:PMCC

Flash Point:>199F

Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM

Fire Fighting Procedures:WEAR SCBA & FULL PROTECTIVE EQUIPMENT. WATER SPRAY MAY BE INEFFECTIVE. FOG NOZZLES ARE PREFERABLE. USE WATER TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE DUE TO THE BUILD-UP PRESSURE WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE WITH INERT ABSORBENT.

## Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.  
DON'T TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDRE USE ONLY  
WITH ADEQUATE VENTILATION.

Other Precautions:AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT  
W/SKIN & EYES. WASH HANDS AFTER USING. PROTECT AGAINST DUST WHICH  
MAY BE GERATED BY SANDING OR ABRADING THE DRIED FILM.

## Exposure Controls

Respiratory Protection:WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA  
IF >TLV.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RECOMMENDED

Eye Protection:SAFETY SPECTACLES

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.

Supplemental Safety and Health

ETHYLENE GLYCOL IS CONSIDERED AN ANIMAL TERATOGEN. IF HAS BEEN SHOWN TO  
CAUSE BIRTH DEFECTS IN RATS & MICE AT HIGH DOSES WHEN GIVEN IN  
DRINKING WATER/GAVAGE. NO EVIDENCE OF BIRTH EFFECTS IN HUMANS. RA  
TS EXPOSED TO TITANIUM DIOXIDE DUST DEVELOPED LUNG CANCER, HOWEVER,  
SUCH EXPOSURE LEVEL IS NOT ATTAINABLE IN WORKPLACE.

## Chemical Properties

Boiling Pt:B.P. Text:212-448F

Vapor Density:>AIR

pH:9.0

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:LIGHT GRAY LATEX GLOOS ENAMEL PAINT

Percent Volatiles by Volume:62-70%

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT, SOURCES OF IGNITION

Hazardous Decomposition Products:CO<sub>2</sub>, CO, OXIDES OF METALS

## Disposal

Waste Disposal Methods:WASTE MUST BE TESTED FOR EXTRACTABILITY TO  
DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. INCINERATE IN  
APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINER. DISPOSE OF IN  
ACCORDANCE WITH FEDER AL, STATE & LOCAL REGULATIONS  
REGARDINGPOLLUTION

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.