

DYNA-BOND PLUS CAT ADH

MSDS Number

BJDDS

National Stock Number

6520-00F011197

Product Name

DYNA-BOND PLUS CAT ADH

Manufacturer

UNITEK CORP

Product Identification

Product ID:DYNA-BOND PLUS CAT ADH

MSDS Date:02/01/1988

FSC:6520

NIIN:00F011197

MSDS Number: BJDDS

Responsible Party

UNITEK CORPORATION

2724 SOUTH PECK ROAD

MONROVIA , CA 91016

Emergency Phone: (818) 574-4000

Info Phone: (818) 574-4000

Cage: 90444

Contractor

UNITEK CORPORATION

MONROVIA, CA 91016-5005

(213) 445-7960

Cage: 90444

Ingredients

BISPHENOL A GLYCIDYLMETHACRYLATE, BIS-GMA

CAS: 1565-94-2

RTECS: UD3438000

TRIETHYLENE GLYCOL DIMETHACRYLATE

CAS: 15625-89-5

RTECS: AT4810000

BENZOYL PEROXIDE, DI-BENZOYLPEROXIDE

CAS: 94-36-0

RTECS: DM8575000

Fraction By Weight: 5%

OSHA PEL5 MG/CUM

ACGIH TLV: 5 MG/CUM

Hazards

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: MAY CAUSE MINOR IRRITATION & REDNESS. SKIN: PROLONGED/REPEATED CONTACT TO UNPOLYMERIZED MATERIAL MAY CAUSE IRRITATION & ALLERGIC SENSITIZATION. INGESTION: THIS MATERIAL MAY BE A SLIGHT HEALTH HAZARD.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYE: MAY CAUSE MINOR IRRITATION & REDNESS. SKIN: PROLONGED/REPEATED CONTACT TO UNPOLYMERIZED MATERIAL MAY CAUSE IRRITATION & ALLERGIC SENSITIZATION. INGESTION: THIS MATERIAL MAY BE A SLIGHT HEALTH HAZARD.
Medical Condition Aggravated by Exposure:ALLERGIC SENSITIZATION

First Aid

First Aid:EYE: WASH W/LARGE QUANTITIES OF LUKEWARM WATER FOR 15 MINUTES. CONTACT PHYSICIAN. SKIN: WASH W/SOAP & WATER THEN FLUSH W/LUKEWARM WATER FOR 15 MINUTES. INGESTION: CONTACT PHYSICIAN.

Fire Fighting

Flash Point:>240F
Extinguishing Media:DRY CHEMICAL, CO2, FOAM
Unusual Fire/Explosion Hazard:LARGE CONTAINERS OF BULK MATERIAL MAY RUPTURE WHEN EXPOSED TO HEAT. SEALED CONTAINER MAY RUPTURE EXPLOSIVELY.

Accidental Release

Spill Release Procedures:CLEAN UP SMALL SPILLS W/PAPER TOWELS.

Handling

Handling and Storage Precautions:STORE IN A COOL

Exposure Controls

Respiratory Protection:GENERALLY NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.
Ventilation:GENERAL AREA VENTILATION
Eye Protection:AS NECESSARY TO PREVENT EXCESSIVE
Supplemental Safety and Health

Chemical Properties

Spec Gravity:1.34
Evaporation Rate & Reference:(BU AC = 1): Solubility in Water:SLIGHT
Appearance and Odor:VISCOUS TRANSLUCENT PASTE, MILD ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, PEROXIDES, STRONG ALKALIES
Stability Condition to Avoid:HEAT & DIRECT SUNLIGHT. STORE >100F.
Hazardous Decomposition Products:TOXIC FUMES

Disposal

Waste Disposal Methods:UNIVERSAL OR BASE ADHESIVE & CATALYST ADHESIVE SHOULD BE MIXED/ALLOWED TO GEL/CURE. USE PROPER LANDFILL DISPOSAL OR INCINERATION. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.