

FLEXFRAM 605 PT A

MSDS Number

BJDMS

National Stock Number

8030-00-097-9088

Product Name

FLEXFRAM 605 PT A

Manufacturer

FIBER MATERIALS INC

Product Identification

Product ID:FLEXFRAM 605 PT A

MSDS Date:11/18/1992

FSC:8030

NIIN:00-097-9088

Kit Part:Y

MSDS Number: BJDMS

Responsible Party

FIBER MATERIALS, INC.

5 MORIN ST

BIDDEFORD , ME 04005

US

Emergency Phone: 207-282-5911;207-828-6209

Info Phone: 207-282-5911

Cage: KO060

Contractor

FIBER MATERIALS, INC.

BIDDEFORD, ME 04005

US

207-282-5911

Cage: KO060

Ingredients

TRIETHYLENETETRAMINE; (TETA (TRIETHYLENETETRAMINE 70%)).

CAS: 112-24-3

RTECS: YE6650000

Fraction By Weight: 7.0%

OSHA PELN/K

ACGIH TLV: N/K

Hazards

LD50 LC50 Mixture:INGREDIENT 1

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE SKIN BURNS, ALLERGIC SKIN REACTIONS. INGESTION MAY CAUSE BURNS OF MOUTH AND THROAT. MAY CAUSE RESPIRATORY SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS OR THROAT IRRITATION.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:PRIMARY IRRITATION OF SKIN ON PROLONGED CONTACT. IRRITATING TO THE EYES. MAY CAUSE SEVERE IRRITATION WITH CORNEAL INJURY, EVEN BLINDNESS.
Medical Cond Aggravated by Exposure:ALLERGIES AND/OR OTHER RESPIRATORY CONDITIONS.

First Aid

First Aid:INHAL: REMOVE TO FRESH AIR, GET MD. EYE: FLUSH THOROUGHLY W/WATER 30 MIN. GET MD IMMEDIATELY. SKIN: WASH W/SOAP AND WATER. INGEST: INDUCE VOMITING AND GET MD IMMEDIATELY.

Fire Fighting

Flash Point Method:COC
Flash Point:315F,157C
Extinguishing Media:CO*2, DRY CHEMICAL
Fire Fighting Procedures:FOR LARGE FIRES, USE WATER SPRAY, FOG, OR FOAM. DIKE WATER RUN-OFF. PREVENT ENTRY INTO SEWERS OR NATURAL WATERS. WEAR FULL PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:TOXIC FUMES WILL BE EVOLVED IF UNMIXED MATERIAL IS INVOLVED IN A FIRE. WEAR SCBA.

Accidental Release

Spill Release Procedures:DIKE. NIOSH APPROVED RESP PROT AND OTHER PROT EQUIP AS NECESSARY TO PREVENT SKIN & EYE CONTACT. PUMP OR SHOVEL INTO SALVAGE DRUM. SOAK UP RESIDUE & SML SPILLS W/ABSORBENT MAT SUCH AS CLAY & PUT IN TIG HT CONTAINER. IF USE SOLVNT, WATCH FIREHAZARDS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE IN TIGHT, STURDY CONTAINERS. HANDLE I/A/W HAZARD POTENTIAL.
Other Precautions:REMOVE CONTAMINATED CLOTHING & PROTECTIVE GEAR. DECONTAMINATE. DESTROY LEATHER ARTICLES, INCLUDING SHOES THAT CANNOT BE DECON. ANSI CLASSIFICATION 2. REMOVAL OF CURED MATERIAL SHOULD BE ACCOMPLISHED W /NIOSH APPROVED RESPIRATORS.

Exposure Controls

Respiratory Protection:NIOSH APPROVED RESP W/ORGANIC VAPOR CARTRIDGE AS REQUIRED TO PREVENT VAPOR OVEREXPOSURE.
Ventilation:LOCAL: IN CONFINED MIXING & APPL. AREAS. MECH: REQUIRED TO PREVENT OVEREXPOSURE.
Protective Gloves:RUBBER GLOVES TO PREVENT SKIN CONTACT.
Eye Protection:GOGGLES OR FACE SHIELD.
Other Protective Equipment:AS NECESSARY TO PREVENT BODY CONTACT. EYE WASH & DELUGE SHOWER .
Work Hygienic Practices:AVOID SMOKING, EATING, AND DRINKING IN THE WORK AREA.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt:B.P. Text:600F,316C
Vapor Pres: .01
Vapor Density:9
Spec Gravity:1.201 (H*20=1)
Solubility in Water:SLIGHT
Appearance and Odor:BLACK VISCOUS LIQUID, MERCAPTAN ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, CHLORINATED ORGANIC COMPOUNDS.
Stability Condition to Avoid:REACTS WITH CONSIDERABLE HEAT WITH HOT RESINS.
Hazardous Decomposition Products:CO*2, ALDEHYDES, ACIDS, NO*2, SO*2

Disposal

Waste Disposal Methods:DISPOSE OF I/A/W FED, STATE AND LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.