

DARK OAK STAIN

MSDS Number

BJDSD

National Stock Number

8010-00-281-2072

Product Name

DARK OAK STAIN

Manufacturer

FARWEST PAINT MFG CO

Product Identification

Product ID:DARK OAK STAIN

MSDS Date:02/10/1989

FSC:8010

NIIN:00-281-2072

MSDS Number: BJDSD

Responsible Party

FARWEST PAINT MFG CO

4522 S. 133RD STREET

TUKWILA , WA 98168

US

Emergency Phone: 206-941-1619

Info Phone: 206-244-8844

Cage: 6F266

Contractor

FARWEST PAINT MANUFACTURING CO

TUKWILA, WA 98168

US

206-244-8844

Cage: 6F266

Ingredients

PIGMENTS (CONSIDERED NON-HAZARDOUS WHEN INCORPORATED IN A

LINSEED OIL

Fraction By Weight: 29-34%

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 67-72%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

METAL SOAP DRIERS (VAPOR PRESSURE 2.0 MMHG @ 68 F) (SOLVENT

Fraction By Weight:

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

SUSPENDING AGENTS

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN:

PROLONGED/REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS. INHALE: NASAL & RESPIRATORY IRRIT, POSSIBLE UNCONSCIOUSNESS & EVEN ASPHYXIATION. SWALLOW: CAN CAUSE GASTROINTESTINAL IRRIT. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Effects of Overexposure:EYES: IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: MODERATE IRRITATION. INHALE: EXCESSIVE INHALE OF VAPORS CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION. SWALLOW: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA.

First Aid

First Aid:SKIN:THOROUGHLY WASH AREA W/ SOAP & WATER. REMOVE CONTAMINATED CLOTHES. LAUNDRY CLOTHES BEFORE RE-USE. EYES:FLUSH W/LG AMTS OF WATER LIFTING LIDS, GET MED ATTN. SWALLOW:DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET & GET MED ATTN. ASPIRATION DUE TO VOMITING CAN CAUSE CHEM PNEUMONITIS WHICH CAN BE FATAL. INHALE:REMOVE PERSON TO FRESH AIR. IF BREATHING DIFFICULT, ADMINISTER OXYGEN. IF STOPPED ADMINISTER CPR. GET MED ATTN.

Fire Fighting

Flash Point Method:TCC

Flash Point:100 F/38 C

Extinguishing Media:FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:NEVER USE NEAR OR AROUND WELDERS OR CUTTING TORCHES. PRODUCT DRUMS (EVEN EMPTY DRUMS FROM JUST THE RESIDUE) CAN IGNITE EXPLOSIVELY.

Accidental Release

Spill Release Procedures:SML:ABSORB ON PAPER, VERMICULITE, ETC. & TRANSFER TO HOOD. LG:ELIMINATE ALL IGNITE SOURCES. WEAR PROTECTIVE EQUIP. STOP SPILL AT SOURCE, DIKE AREA. PUMP LIQUID TO SALVAGE TANK, REMAINDER TAKE UP W/SAND, ETC. PREVENT RUN OFF TO SEWERS & OTHER BODIES OF WATER. *

Neutralizing Agent:N/A. *IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, A SPILL OCCURRED.

Handling

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, &/OR SOLID).

Other Precautions:ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

Exposure Controls

Respiratory Protection:A JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATOR UNDER SPECIFIED CONDITIONS. (SEE YOUR

SAFETY EQUIP SUPPLIER)ENGINEER ING/ADMIN CONTROLS SHOULD BE IMPLEMENTED

Ventilation:SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST)

VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:WEAR RESISTANT GLOVES (NITRILE RUBBER)

Eye Protection:CHEM SPLASH GOGGLES, SAFETY GLASSES.

Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN

CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices:KEEP WORK AREA CLEAN, FREE FROM LEAKS & SPILLS.

ALWAYS WASH HANDS THOROUGHLY W/SOAP & WATER BEFORE HANDLING

FOOD/DRINKS

Supplemental Safety and Health

"PURSUANT TO TITLE III OF THE SUPERFUND AMMENDMENTS & REAUTHORIZATION

ACT OF 1986 (SARA) & 40 CFR PART 372, THIS PRODUCT CONTAINS OR MAY

CONTAIN A TOXIC CHEMICAL IN A QUANTITY SUBJECT TO THE REPORTING

REQUIREMENTS UNDER SECTION 313."

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Density:> THAN AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORED THIN LIQUID WITH A MILD SWEET AROMATIC

ODOR.

Percent Volatiles by Volume:68-70

Stability

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:KEEP AWAY FROM OPEN FLAMES, SPARKS AND

HEAT. DO NOT WELD NEAR OR AROUND PRODUCT.

Disposal

Waste Disposal Methods:DESTROY BY LIQUID INCINERATION. CONTAMINATED

ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL,

STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.